

## T7299-T

### Description

15A-125V, Tamper Resistant, Smart Lock Pro Combination GFCI .Single outlet with a switch, monochromatic, wallplate and screws included – Light Almond

### Product Features



**Color:** Light Almond



**NEMA:** 5-15R



Grounding: GFCI Ground Fault

Feature: SmartLockPRO Combo Receptacle and Single-Pole Switch

Amperage: 15 Amp

Voltage: 125 Volt

NEMA: 5-15R

Pole: 2

Wire: 3

Termination: Back & Side 20A Feed-Thru

Face Material: Nylon

Body Material: Polycarbonate

Strap Material: Steel

Color: Light Almond

Standards and Certifications: UL/CSA

Warranty: 2-Year Limited

Diagnostics: w/ Indicator Light

### Features and Benefits

- Replaces standard switch/outlet combination devices in residential or light commercial installations
- Permits multiple wiring options that allow for GFCI protection of switched load and downstream receptacles
- Automatically test the GFCI every time the RESET button is pushed in. The GFCI will not reset if the GFCI circuit is not functioning properly
- By blocking reset of the GFCI if protection has been compromised, SmartLockPRO reduces the possibility of end-users incorrectly assuming that a reset GFCI outlet is providing ground fault protection when it actually is not.
- A line-load reversal diagnostic feature is provided which prevents the GFCI from being reset and stops power from being fed to the GFCI receptacle face or through to downstream devices. A green LED indicator on the GFCI's face also illuminates to alert the installer to the line-load wiring reversal.
- The trip latch mechanism in SmartLockPro GFCIs is a one piece "T" design for efficient operation
- Trip threshold meets or exceeds UL requirements for tripping time
- Improved immunity to high-frequency noise reduces nuisance tripping
- Advanced electronics design provides superior resistance to electrical surges and over-voltages
- Expanded wiring options with nine back-wire holes (two for each line and load connection plus one for ground with an internal clamp)
- Silver alloy contacts
- Compatible with all Decora devices and wallplates; available in select Decora colors

| AC Horsepower Ratings        |  |
|------------------------------|--|
| At Rated Voltage             | 1 HP                                     |
| Environmental Specifications |  |
| Flammability                 | Rated V-2 per UL94                       |
| Operating Temperature        | -35C to 65C                              |
| Mechanical Specifications    |  |
| Terminal ID                  | Brass-Hot, Green-Ground, Silver-Neutral  |
| Product ID                   | Ratings are permanently marked on device |
| Standards and Certifications |  |
| NEMA                         | WD-1 & WD-6                              |
| ANSI                         | C-73                                     |
| UL 943                       | Class A (GFCI)                           |
| UL 498                       | File E-48380                             |
| CSA C22.2 No. 42             | File LR-57811                            |
| NOM                          | 057                                      |

| Electrical Specifications |   |
|---------------------------|---|
| Temperature Rise          | 80°C max at full rated current after 50 cyc OL at 150% rated current for both AC and DC per UL498 |
| Material Specifications   |   |
| Face Material             | Nylon   |
| Body Material             | Polycarbonate   |
| Terminal Screws           | Brass 8-32  |
| Grounding Screw           | Brass 8-32  |
| Yoke                      | Zinc-Plated Steel   |
| Clamp Nuts                | Steel   |
| Performance Data          |   |
| Diagnostics               | w/ Indicator Light  |
| Trip Level                | 5mA plus or minus 1mA   |

#### SPECIFICATION SUBMITTAL

|                      |                      |                      |
|----------------------|----------------------|----------------------|
| JOB NAME:            | CATALOG NUMBERS:     |                      |
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| JOB NUMBER:          | <input type="text"/> | <input type="text"/> |

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

#### Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2007-2010 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

