
# **Category 6A Shielded Modular Connector**

### PRODUCT SPECIFICATION



## Package includes:

- A. Category 6A Shielded Modular Connector, 1 pc
- B. Wire Termination Cap, 1 pc
- C. Cable Tie, 1 pc




#### **Features and Benefits:**


- CAT 6A shielded connectors provide excellent performance for data networks requiring maximum speed and bandwidth.
- Lead frame technology provides maximum performance and uninterruptible signal integrity.
- Enhanced crosstalk cancellation reduces return loss and improves performance by rejecting noise and unwanted signals.
- Exceeds TIA 568-B.2-10 Category 6A connecting hardware requirements.
- Engineered to provide wire termination cap for a quick and easy termination.
- Shielded housing provides against electro-magnetic interference (EMI).
- Compatible with TIA-568A/B wiring diagram.
- Ideal for 22~24AWG
- UL listed.


MODULE, CAT 6A, FTP			<b>Sec</b>
ITEM NO.	IC1078S6A0	REV. B	<u>Premium<b>Products</b></u>
DWG NO.	PS1078S6A0	PAGE NO. 1	<u>Proven <b>Performance</b></u> Competitive <b>Prices</b>


CUSTOMER CARE / TECHNICAL SUPPORT \* CSR@ICC.COM / 888-ASK-4-ICC (275-4422) \* 14700 Alondra Blvd., La Mirada, CA 90638 \* www.icc.com












#### **NOTE: UNLESS OTHERWISE SPECIFIED**

- 1. CAT6A FTP MODULAR CONNECTOR:
  - A. ENVIRONMENTAL CONDITIONS:
    - -TEMPERATURE RANGE
    - -STORAGE:-40 TO +70¢XC, OPERATIONAL:-10 TO +60¢XC
    - -RELATIVE HUMIDITY (OPERATIONAL): MAXIMUM NONCONDENSING 93%
  - B. ELECTRICAL:
    - -INSULATION RESISTANCE: 500 MEGAOHM MIN
    - -CONTACT RESISTANCE: 20 MILLIOHM MAX
    - -DIELECTRIC WITHSTANDING VOLTAGE: 1,000 VOLTS D.C., 60 HZ, 1 MIN
  - C. MECHANICAL:
    - -TOTAL CONTACT FORCE: 800 GRAM FOR 8 WIRE LEADS MINIMUM
    - -RETENTION: 50N (11 LBF) FOR 60S±5S
    - -INSERTION LIFE: 750 CYCLES MIN
  - D. PHYSICAL:
    - -HOUSING: ZINC-ALLOY FULLY SHIELDED
    - -SPRING WIRE: PHOSPHOR BRONZE ALLOY PLATED WITH 50 MICRO-INCH
    - OF GOLD OVER 70~100 MICRO-INCH OF NICKEL
- 2. WIRE TERMINATION CAP: ABS
- 3. IDC WIRE GAUGE: 22~24 AWG

#### WIRING LABEL







MODULE, CAT 6A, FTP			
ITEM NO.	IC1078S6A0	REV. B	
DWG NO.	PS1078S6A0	PAGE NO. 2	



CUSTOMER CARE / TECHNICAL SUPPORT \* CSR@ICC.COM / 888-ASK-4-ICC (275-4422) \* 14700 Alondra Blvd., La Mirada, CA 90638 \* www.icc.com