
62.5/125µm Multimode SC-Simplex MPO Cassette

PRODUCT SPECIFICATION



Features and Benefits:

- High quality aluminum material allows for compact and durable cassettes.
- Cassette offers a plug and play solution which saves assembly and termination time.
- Designed to fit ICC's wall mount enclosures (ICFOD) and rack mount enclosures (ICFOR).

6X SC Simplex Adapters


- MPO connector reduces insertion loss which enhances channel link performance.
- Suitable for any applications with a need for higher bandwidth with longer distances.
- Cassette allows up to 18 fibers within 1 RMS.
- Available in black only.


MPO CASSETTE, SC-SIMPLEX, MM, 62.5/125μm

ITEM NO.	ICFC06MSS6	REV. C
DWG NO.	PSFC06MSS6	PAGE NO. 1



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com





NOTE: UNLESS OTHERWISE SPECIFIED

- 1. CASSETTE HOUSING:
 - A. MATERIAL: ALUMINUM ALLOY
 - B. SURFACE FINISHING: BLACK POWDER COAT
- 2. SC-SIMPEX CONNECTOR:
 - A. MATERIAL: ABS
 - B. COLOR:

HOUSING: BEIGE CAP: BEIGE

C. SLEEVE: CERAMIC

D. INSERTION LOSS: <=0.3 dB (1300nm) E. OPERATING TEMPERATURE: -20°~ 70° F. STORAGE TEMPERATURE: -40°~ 80°

3. MPO ADAPTER:

A. MATERIAL: POLYBUTYLENE TEREPHTHALATE (PBT)

B. INSERTION LOSS: <0.5dB (1310nm)

C. COLOR: BLACK

D. MATING CYCLES: 1000 MATING CYCLES

E DUST CAP: TPR COLOR: BLACK



MPO CASS	SETTE, SC-SIMPL	LEX, MM, 62.5/125μm
ITEM NO.	ICFC06MSS6	REV. C

		-
ITEM NO.	ICFC06MSS6	REV. C
DWG NO.	PSFC06MSS6	PAGE NO. 2



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com