

Ortronics

OR-PHD5E6U24

## Clarity5E 24-port panel, Cat 5e, high density, six-port modules, 19" x 1.75" - OR-PHD5E6U24

Clarity<sup>5E</sup> 24-port panel, Cat 5e, high density, six-port modules, 19 x 1.75"



### FEATURES

- ETL verified to TIA Category 5e component spec
- Center tuned to Clarity<sup>5E</sup> patch cords
- Universal wiring
- Easy lace 110 termination
- Supplied rear cable management
- High density design
- RoHS compliant

### BENEFITS

- Elevated component performance
- More transparent mated union
- Supports T568A and T568B installs
- Saves installation time
- Supports good cabling practice
- Maximizes rack utilization
- Lead free

## Specifications

### DIMENSION INFO

Height Metric: 44.45 mm

Width Metric: 482.6 mm

Cable Diameter Range: 22-26 AWG

Depth Metric: 3.175 mm

Height U S: 1.75 in

### GENERAL INFO

Mod Jack Wiring: Universal T568A/B

Number Of Ports: 24

### TECHNICAL INFO

Performance Rating: Category 5e

Category Rating: Category 5e

### CONSTRUCTION INFO

Component1: Panel - Material1: .094" Aluminum, Finish\_Plating1: Painted black texture with green silkscreen

Component4: Array of eight modular dual reactance contacts - Material4: Beryllium copper, Finish\_Plating4: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Component5: IDC contacts (low noise) - Material5: Phosphor Bronze, Finish\_Plating5: Nickel plating with tin over plate

### BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant