
FIRE CLASSIFIED OMNIBOX SERIES STANDARD DEPTH STEEL FLOOR BOXES ORDERING INFORMATION

880M1FC 4 13/16" 2 15/16" [75mm] 3 23/32" [94mm] 23" [584mm]

ONE-GANG STANDARD DEPTH STEEL FLOOR BOX -

Adjustment range over deck of 3 1/4" [83mm] minimum to 4" [102mm] maximum. Use in light weight concrete 3 1/4" [83mm] minimum pour over deck. One 1 1/4" [32mm] conduit feed opening. Box Capacity - 37 cubic inches.


NOTE: FLoor Box spacing 2' on center and one for every 4 square feet in a span.
Four (4) #12 AWG Type THHN Power Conductors or 48 #23 AWG (6 Cat. 6)
Tele Data Conductors per gang.



TWO-GANG STANDARD DEPTH STEEL FLOOR BOX -

Adjustment range over deck of 3 1/4" [83mm] minimum to 4" [102mm] maximum. Use in light weight concrete 3 1/4" [83mm] minimum pour over deck. Two 1 1/4" [32mm] conduit feed openings. Box Capacity - 40 cubic inches each gang.

NOTE: FLoor Box spacing 2' on center and one for every 4 square feet in a span. Four (4) #12 AWG Type THHN Power Conductors or 48 #23 AWG (6 Cat. 6) Tele Data Conductors per gang.




THREE-GANG STANDARD DEPTH STEEL FLOOR BOX -

PART NO.

Adjustment range over deck of 3 1/4" [83mm] minimum to 4" [102mm] maximum. Use in light weight concrete 3 1/4" [83mm] minimum pour over deck. Three 1 1/4" [32mm] conduit feed openings. Inside Gang Capacity - 45 cubic inches. Outside Gang Capacity - 36 cubic inches each gang.

NOTE: FLoor Box spacing 2' on center and one for every 4 square feet in a span. Four (4) #12 AWG Type THHN Power Conductors or 48 #23 AWG (6 Cat. 6) Tele Data Conductors per gang.

COVER PLATE FLANGES FOR FIRE CLASSIFIED OMNIBOX SERIES FLOOR BOXES ORDERING INFORMATION



DESCRIPTION FLANGE -

One-gang brass (817B) or brushed aluminum (818TCAL) combination carpet and tile flange. Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II, and Wiremold CM Series Open System adapters. All sold separately.

FLANGE	Α		В	
818TCAL	5.940"	[150.9mm]	4.920"	[125.0mm]
817B	6.080"	[154.4mm]	5.060"	[128.5mm]

NOTE: Brushed aluminum flanges come with beveled edges.



FLANGE -

Two-gang brass (827B) or brushed aluminum (828TCAL) combination carpet and tile flange. Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II, and Wiremold CM Series Open System adapters. All sold separately.

FLANGE	Α		В	
828TCAL	5.940"	[150.9mm]	9.045"	[229.7mm]
827B	6.080"	[154.4mm]	9.185"	[233.3mm]

NOTE: Brushed aluminum flanges come with beveled edges.


NOTE: UL Listed for tile, terrazzo, wood, and carpet floors.

Brass covers and flanges are not interchangeable with aluminum covers and flanges.

CODE REFERENCE

cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT.

Meets Article 314.27(C) of NEC.




FLANGE -

Three-gang brass (837B) or brushed aluminum (838TCAL) combination carpet and tile flange. Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II, and Wiremold CM Series Open System adapters. All sold separately.

DESCRIPTION

FLANGE	Α		В	
838TCAL	5.940"	[150.9mm]	13.170"	[334.5mm]
837B	6.080"	[154.4mm]	13.310"	[338.1mm]


NOTE: Brushed aluminum flanges come with beveled edges.



FLANGE -

One-gang brass carpet flange. For use on 880S1FC and 880M1FC Floor Boxes.


NOTE: Brushed aluminum flanges come with beveled edges.



LANGE -

Two-gang brass carpet flange. For use on 880S2FC and 880M2FC Floor Boxes.

NOTE: Brushed aluminum flanges come with beveled edges.



FLANGE -

Three-gang brass carpet flange. For use on 880S3FC and 880M3FC Floor Boxes.

NOTE: Brushed aluminum flanges come with beveled edges.



