



by **Schneider** Electric

# Switched Rack PDU

## Overview


The American Power Conversion (APC®) Switched Rack Power Distribution Unit (PDU) is a network-manageable device that allows individual outlet control. You can configure and monitor it over the network, and you can monitor its aggregate current draw both remotely and locally through the digital display.

**Outlets.** The Rack PDU has twenty-four (24) NEMA 5-20 outlets.

**Power cord.** The 10-foot (3.05-meter) cord terminates with a NEMA L5-20 connector.

**Digital display.** The digital display allows you to monitor the aggregate current of the Rack PDU and to establish a network connection using the network port.

## AP7930



Sold by:



**TWAcomm.com**  
<http://www.TWAcomm.com>  
Toll Free: (877) 389-0000


by **Schneider** Electric

# Specifications

## Electrical

Input connector	NEMA L5-20 plug
Output connectors	(24) NEMA 5-20 outlets
Cord length	10 ft (3.05 m)
Nominal input voltage	120 VAC
Acceptable input voltage	± 10 % of nominal voltage
Input frequency	50/60 Hz

## Physical

Dimensions (H × W × D)	63.75 x 2.19 x 1.73 in (161.92 x 5.56 x 4.39 cm)
Shipping dimensions (H × W × D)	84.00 x 6.00 x 5.00 in (213.36 x 15.24 x 12.70 cm)
Weight	13.00 lb (5.90 kg)
Shipping weight	15.00 lb (6.80 kg)

## Environmental

Maximum elevation (above MSL)	
Operating	10,000 ft (3000 m)
Storage	50,000 ft (15 000 m)
Temperature	
Operating	23 to 113° F (–5 to 45° C)
Storage	–13 to 149° F (–25 to 65° C)
Humidity	
Operating	5 – 95%, non-condensing
Storage	5 – 95%, non-condensing

## Compliance

EMC verification	FCC Part 15 Class A ICES-003
Safety verification	UL/cUL Listed

Customer support and warranty information is available at the APC Web site,  
**[www.apc.com](http://www.apc.com)**.

© 2008 American Power Conversion. All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners.


**990-1767C**  
**11/2008**
