

Clauss® **ANTI-WICKING TOOLS**

- Precision-made from non-fatiguing copper/beryllium alloy.
- Fully chrome-plated for extended life and solder-free operation.
- Heads drilled to precise tolerances for positive conductor contact and maximum thermal conductivity.
- Insures compliance with military and NASA specifications on inspection requirements of solder connections when used properly.
- Reverse action automatically grips conductor.
- Stock numbers give correct AWG size wire that tools are made to fit.
- Meet all specifications for soldering both single and multi-strand wire.



AW SERIES



STOCK NO.*	FULL LENGTH IN / MM	CONDUCTOR CONTACT LENGTH IN / MM	HOLE DIAMETER IN / MM
AW 18	5" - 127mm	1/16" - 1.59mm	.046 - .047" - 1.17 - 1.19mm
AW 20	5" - 127mm	1/16" - 1.59mm	.035 - .036" - .89 - .91mm
AW 22	5" - 127mm	1/16" - 1.59mm	.028 - .029" - .71 - .74mm
AW 24	5" - 127mm	1/32" - .79mm	.022 - .023" - .56 - .58mm
AW 26	5" - 127mm	1/32" - .79mm	.017 - .018" - .43 - .46mm
AW 28	5" - 127mm	1/32" - .79mm	.012 - .014" - .30 - .36mm
AW 30	5" - 127mm	1/32" - .79mm	.010 - .011" - .25 - .28mm



STOCK NO.*	FULL LENGTH IN / MM	CONDUCTOR CONTACT LENGTH IN / MM	HOLE DIAMETER IN / MM
AWG 18	4 1/2" - 114mm	1/16" - 1.59mm	.046 - .047" - 1.17 - 1.19mm
AWG 20	4 1/2" - 114mm	1/16" - 1.59mm	.035 - .036" - .89 - .91mm
AWG 22	4 1/2" - 114mm	1/16" - 1.59mm	.028 - .029" - .71 - .74mm
AWG 24	4 1/2" - 114mm	1/32" - .79mm	.022 - .023" - .56 - .58mm
AWG 26	4 1/2" - 114mm	1/32" - .79mm	.017 - .018" - .43 - .46mm
AWG 28	4 1/2" - 114mm	1/32" - .79mm	.012 - .014" - .30 - .36mm
AWG 30	4 1/2" - 114mm	1/32" - .79mm	.010 - .011" - .25 - .28mm

AWG SERIES



* Stock numbers give correct wire size tools are made to fit.

ANTI-WICKING TOOLS