









**TechChoice® structured cabling solutions** combine the reliability and ease of installation you'd expect from Legrand/Ortronics with quality performance and rugged construction to provide a cost-effective option for communications technicians.

Products are third party tested to meet Category 5e and 6 specifications for TIA/EIA-568-B.2 and ISO11801-2002.

## The TechChoice



## end-to-end solution



When integrated into our standard line of physical support and combined with our fiber offering, TechChoice provides a solid end-to-end infrastructure solution for everyday opportunities.

#### Warranty

A 15-year product and applications assurance warranty is available for all qualifying installations,\* offering additional value and piece of mind when selecting TechChoice.

\*When installed by a Legrand
Data Communications certified installer
using an approved cable manufacturer.



#### WORKSTATION






OR-KS6

OR-KSRJ25

#### **KEYSTONE JACKS**

TechChoice keystone jacks and modules feature an easyto-follow universal wiring label and support standard termination using a 110impact tool. The keystone footprint allows for the greatest flexibility in installation scheduling because its rear insertion into the faceplate allows the technician to complete the termination before, during and after the construction process.

PART NO. Single Pack	PART NO. Pack of 25	DESCRIPTION
OR-KS6A	OR-KS6	Category 6, 8-position, 180° exit, T568A/B wiring, icon compatible
OR-KS5EA	OR-KS5E	Category 5e, 8-position, 180° exit, T568A/B wiring, icon compatible
OR-KSRJ25A	OR-KSRJ25	Category 5e, 8 position jack, T568A/B icon compatible
	OR-KSICON	TechChoice keystone icon compatible 2 sided voice/data



-00=Black; -13=Electrical ivory; -36=Blue; -42=Red; -88=Cloud white; -99=Wiremold® ivory; -43=Orange; -44=Yellow, -45=Green; -78=Gray. Standard color is fog white, requiring no tail code.



OR-KSST



#### **FIBER KEYSTONE MODULES**

	PART NO.	DESCRIPTION
	OR-KSST	1-ST simplex multimode, phosphor-bronze alignment sleeves, 180° exit. Fog white. Sold with dust cover
	OR-KSSC	1-SC simplex multimode, phosphor-bronze alignment sleeves, 180° exit. Fog white. Sold with dust cover
OI	OR-KSLC	1-LC (2 fibers) multimode, phosphor-bronze alignment sleeves, 180° exit. Fog white. Sold with dust cover

NOTE: For Wiremold Ivory, add tail code of -99 to end of part number (example OR-KSST-99) Sold individually.





OR-KSRCAR



OR-KSSV

#### **MULTIMEDIA KEYSTONE MODULES**

PART NO.	DESCRIPTION
OR-KSFCN*	F-connector, F/F, 75 ohm
OR-KSRCAR	RCA (red insulator), 110 termination
OR-KSRCAB	RCA (black insulator), 110 termination
OR-KSRCAY	RCA (yellow insulator), 110 termination
OR-KSRCAG*	RCA (green insulator), 110 termination
OR-KSRCABL*	RCA (blue insulator), 110 termination
OR-KSRCAW*	RCA (white insulator), 110 termination
OR-KSBP	Binding posts, pair of speaker terminals (one red, one black)

NOTE: Standard color is fog white. Add -99 for Wiremold ivory. \*Also available in -88 cloud white and -13 electrical ivory. OR-KSFCN also available in 25 pack (KSFCN25pk) For other colors, contact sales.







OR-KSUSBAA



OR-KS35STST

#### ADDITIONAL MULTIMEDIA JACKS

PART NO.	DESCRIPTION
OR-KSSV	S-Video, 110 termination
OR-KSSVIDC**	S-Video, F/F
OR-KSBNC	BNC connector, 50 ohm, F/F
OR-KSBNC75	BNC Connector, 75 ohm, F/F
OR-KSHDMI**	HDMI, F/F
OR-KSUSBAA**	USB 2.0, Type A to A, F/F
OR-KSUSBAB**	USB 2.0, Type A to B, F/F
OR-KS35STST	3.5mm, audio, screw termination
OR-KS35ST*	3.5mm audio jack, F/F
OR-KSB10*	Blank, package of ten

<sup>\*</sup>Also available in -88 cloud white and -13 electrical ivory. OR-KSFCN also available in 25 pack (KSFCN25pk) For other colors, contact sales.



#### **SERIES II® BEZEL**

Ortronics® Series II bezel integrates the popular Series II faceplate with all Tech-Choice connectivity options. This combination allows for a broad range of A/V and data connectivity configurations in one faceplate. Each bezel holds two TechChoice keystone jacks or modules.

PART NO.	DESCRIPTION
OR-KSS2210	Series II bezel (1U) holds two TechChoice keystone jacks or modules



OR-KSFP4V110

#### **VGA FACEPLATES**

VGA Faceplates are available in high impact 94V-0 rated thermoplastic. The single gang version includes one integrated VGA connector. The double gang version includes two VGA connectors.

PART NO.	DESCRIPTION
OR-KSFP4V110	Single-gang, holds four keystones, VGA to 110
OR-KSFP4VFT	Single-gang, holds four keystones, VGA with crimp pins
OR-KSFP8V110	Double-gang, holds eight keystones, two VGA to 110
OR-KSFP8VFT	Double-gang, holds eight keystones, two VGA with crimp pins

NOTE: Standard color is fog white. Add -13 for electrical ivory.



#### Designing a pathway system for multi-media needs

Legrand's Wiremold® pathway systems for infloor, perimeter, open space and vertical applications take into consideration and provide the proper space, capacity and bend radius for mixed A/V, data communications and electrical applications. All Wiremold pathways are designed to seamlessly integrate the complete line of TechChoice connectivity for audio, video and data, allowing for an extensive offering of connections to be brought anywhere they are needed.

<sup>\*\*</sup>Available in December 2009

**FACEPLATES** 

#### WORKSTATION





OR-KSDS4



TechChoice® faceplates are available in high impact 94V-0 rated thermoplastic and stainless steel, with a variety of port capacities to match your workstation applications. All faceplates allow for a flush jack finish.

NOTE: Standard color is fog white. Add -13 for electrical ivory, -88 for cloud white or -99 for Wiremold ivory.

Plastic Faceplates	Stainless Steel Faceplates	DESCRIPTION
OR-KSFP1	OR-KSSS1	Single gang, holds one keystone
OR-KSFP2	OR-KSSS2	Single gang, holds two keystones
OR-KSFP3	OR-KSSS3	Single gang, holds three keystones
OR-KSFP4	OR-KSSS4	Single gang, holds four keystones
OR-KSFP6	OR-KSSS6	Single gang, holds six keystones
OR-KSFP8	OR-KSSS8	Dual gang, holds eight keystones
OR-KSFP12	OR-KSSS12	Dual gang, holds 12 keystones

#### **Plastic Faceplates without Label Fields**

PART NO.	DESCRIPTION
OR-KSFPR1	Single gang with one keystone opening
OR-KSFPR2	Single gang with two keystone openings
OR-KSFPR3	Single gang with three keystone openings
OR-KSFPR4	Single gang with four keystone openings
OR-KSFPR6	Single gang with six keystone openings

#### Plastic Rectangular GFCI & 106 Frames

	•
PART NO.	DESCRIPTION
OR-KSDS2	Stylistic rectangular frame with 2 keystone openings
OR-KSDS3	Stylistic rectangular frame with 3 keystone openings
OR-KSDS4	Stylistic rectangular frame with 4 keystone openings
OR-KS106S2	106 style frame with 2 keystone openings
OR-KS106S4	106 style frame with 4 keystone openings





OR-KSSMB2



OR-KSSMB4



OR-KSSMB6

#### **SURFACE MOUNT BOXES**

TechChoice high impact surface mount boxes accommodate two-, four- or sixport keystone requirements. They are compatible with the Wiremold® Eclipse range of solutions, or can easily be surface installed with supplied screws or double-sided tape. Designation strips and clear covers included.

PART NO.	DESCRIPTION
OR-KSSMB2	Holds two keystones, 2.42" x 2.18" x 1.16"
OR-KSSMB4	Holds four keystones, 4.78" x 3.6" x 1.14"
OR-KSSMB6	Holds six keystones, 6.76" x 3.6" x 1.14"

NOTE: Available in fog white. Product dimensions are listed by length, width and height.



OR-40300630

#### **FURNITURE PLATES**

PART NO.	DESCRIPTION
OR-40300630	Holds four keystones, two-piece base and cover, adjustable to fit a range of common furniture openings (2.67"-2.75" x 1.34"-1.41") for 0.065" thick material

NOTE: Standard color is fog white. Add -00 for black.

# Control of the contro

PANELS & CORDS

#### **PATCH PANELS**

24- and 48-port TechChoice® patch panels are available in the traditional multi-port panel format with 6-port modules for Cat 6 and Cat 5e. Patch panel kits are also available to support individual keystone jacks: Cat 6, Cat 5e and multimedia (sold separately).





	•
PART NO.	DESCRIPTION
OR-SP6U24	24-port, T568A/B, height 1.75", 1 rack unit
OR-SP6U48	48-port, T568A/B, height 3.5", 2 rack units
OR-SPA6U24*	24-port, angled, T568A/B, height 1.75", 1 rack unit
OR-SPA6U48*	48-port, angled, T568A/B, height 1.75", 2 rack units

#### Category 5e with 6-port modules

Category 6 with 6-port modules

category of man a portinionalise		
PART NO.	DESCRIPTION	
OR-SP5EU24	24-port, T568A/B, height 1.75", 1 rack unit	
OR-SP5EU48	48-port, T568A/B, height 3.5", 2 rack units	
OR-SPA5EU24*	24-port, angled, T568A/B, height 1.75", 1 rack unit	
OR-SPA5EU48*	48-port, angled, T568A/B, height 1.75", 2 rack units	

#### Patch Panel Kit (accepts KS series keystone jacks & modules)

PART NO.	DESCRIPTION
OR-SPKSU24	24-port, height 1.75", 1 rack unit
OR-SPKSU48	48-port, height 3.5", 2 rack units
OR-SPAKSU24*	24-port, angled, height 1.75", 1 rack unit
OR-SPAKSU48*	48-port, angled, height 1.75", 2 rack units

<sup>\*</sup>Available December 2009



OR-SPC5E05-05



OR-SPC607-00

#### **MODULAR PATCH CORDS**

TechChoice® patch cords offer a slim design for high density applications and come factory terminated with a snagless boot. Each cable is pre-tested for component performance.

#### Category 6

outegory o			
PART NO. Single Pack	PART NO.  10 Packs	DESCRIPTION	
OR-SPCA603-XX	OR-SPC603-XX	Four pair stranded patch cord PVC, length 3ft	
OR-SPCA605-XX	OR-SPC605-XX	Four pair stranded patch cord PVC, length 5ft	
OR-SPCA607-XX	OR-SPC607-XX	Four pair stranded patch cord PVC, length 7ft	
OR-SPCA610-XX	OR-SPC610-XX	Four pair stranded patch cord, PVC length 10ft	
OR-SPCA615-XX	OR-SPC615-XX	Four pair stranded patch cord, PVC length 15ft	
OR-SPCA625-XX	OR-SPC625-XX	Four pair stranded patch cord, PVC length 25ft	

#### Category 5e

PART NO. Single Pack	PART NO.  10 Packs	DESCRIPTION
OR-SPCA5E03-XX	OR-SPC5E03-XX	Four pair stranded patch cord PVC, length 3ft
OR-SPCA5E05-XX	OR-SPC5E05-XX	Four pair stranded patch cord PVC, length 5ft
OR-SPCA5E07-XX	OR-SPC5E07-XX	Four pair stranded patch cord PVC, length 7ft
OR-SPCA5E10-XX	OR-SPC5E10-XX	Four pair stranded patch cord PVC, length 10ft
OR-SPCA5E15-XX	OR-SPC5E15-XX	Four pair stranded patch cord PVC, length 15ft
OR-SPCA5E25-XX	OR-SPC5E25-XX	Four pair stranded patch cord PVC, length 25ft

NOTE: Available in the following colors: -XX = -00 Black; -02 Red; -04 Yellow; -05 Green; -06 Blue; -08 Gray; -09 White.

Add tailcode to end of part number (example: OR-SPC603-02).

#### PHYSICAL SUPPORT

Complete cable management maximizes system performance. The right cable management can protect and extend the life of a network. Ortronics® broad selection of cable management products meet all cabling requirements while providing strength and support, and flexibility for today's system design and future expansion.



#### Standard EIA Equipment Racks and Vertical Managers

OR-19-84-T2SDB	Homaco 2-Post Standard Equipment Rack, 84.00"H x 20.19"W x 15.00"D, rack spaces: 45, channel width: 3, load rating: 750 lbs, ship weight: 30 lbs
OR-19-96-T2SDB	Homaco 2-Post Standard Equipment Rack, 96.00"H x 20.19"W x 15.00"D, rack spaces: 51, channel width: 3, load rating: 750 lbs, ship weight: 33 lbs
OR-SVMS706	Standard Vertical Cable Management cage with cover, 6.00" x 6.58" x 7', single-sided
OR-SVMS806	Standard Vertical Cable Management cage with cover, 6.00" x 6.58" x 8', single-sided
OR-DVMS706	Standard Vertical Cable Management cage with cover, 6.00" x 13.17" x 7', double-sided
OR-DVMS806	Standard Vertical Cable Management cage with cover, 6.00" x 13.17" x 8', double-sided

#### **Horizontal Managers**

OR-808045590	Cable Management Panel , five horizontal polycarbonate plastic distribution rings, 1.7"H x 6"D, 1 rack unit
OR-808004867	Cable Management Panel, five horizontal plastic distribution rings, 3.95"H x 2.4"D, 2 rack units
OR-MM6HM61RU	Mighty Mo 6 Horizontal Management Panel, Six-port finger spacing, cover, one rack unit (1.75" x 19"), black
OR-MM6HM62RU	Mighty Mo 6 Horizontal Management Panel, Six-port finger spacing, cover, two rack units (3.5" x 19"), black

#### Mighty Mo 6 Rack and Vertical Manager

PART NO.	DESCRIPTION
OR-MM6706	Mighty Mo 6 Cable Management Rack, 6.5" channel depth, 7' high, black, 45 rack units
OR-MM6VMS706	Mighty Mo 6 Vertical Cable Management Cage, with Cover, 6" x 7" x 7'



OR-19-21-T12DB



OR-HFM-19-2



OR-604004301



OR-808004867



OR-7070080

#### **Wall Mount Racks and Brackets**

Wall Mount Racks and Drackets		
OR-19-21-T25D	Swing-EZ Wall Racks, 21.00"H x 19.75"W x 25.00"D, rack spaces (1.75"): 11, load rating: 75 lbs, ship weight: 30 lbs	
OR-19-35-T25D	Swing-EZ Wall Racks, 35.00"H x 19.75"W x 25.00"D, rack spaces (1.75"): 19, load rating: 75 lbs, ship weight: 35 lbs	
OR-19-48-T25D	Swing-EZ Wall Racks, $48.00^{\circ}$ H x $19.75^{\circ}$ W x $25.00^{\circ}$ D, rack spaces (1.75"): 26, load rating: 75 lbs, ship weight: $44$ lbs	
OR-604004301	Hinged Wall Mount Bracket, 19" x 6" x 5.25", 3 rack units	
OR-604004396	Hinged Wall Mount Bracket, 19" x 6" x 3.5", 2 rack units	
OR-604044927	Wall Mount Shelf , 20" x 4.875" x 18", 120 lbs capacity	
OR-HFM-19-2	Cable Management Products fro Swing-Ezs, Front rings: vertical 1.75"W x 3.75"D, front rings: horizontal 1.75"H x 1.75"D, back rings: horizontal 2.50"H x 1.62"D, rack spaces (1.75"): 2, ship weight: 5 lbs	
OR-80804867	Cable Management Products fro Swing-Ezs, five horizontal plastic distribution rings, 3.95"H x 2.4"D, 2 rack units	

#### Accessories

Accessories		
OR-60400533	Panel Mounting Screws, #12-24 x .625", package of 50	
OR-70700080	Color-coded Cable Management Straps 6"L x .75"W, <b>grip range:</b> .625" to 1.625" diameter	
OR-70700079	Color-coded Cable Management Straps, 12"L x .75"W, <b>grip range:</b> 1.25" to 3.25" diameter	
OR-MM6BLC	Bend Limiting Clips, 3.25" long for vertical management cages with door or cover	

#### FIBER SOLUTIONS

Ortronics® fiber optic solutions support common, convenient approaches to fiber optic cabling. Our extensive product range offers design flexibility for efficient solutions that offer quality with ease and speed of installation.

For more product selections, please call your local Ortronics representative.



#### **Wall Mount Fiber Cabinet**

Patch cabinet: Holds two adapter panels ST, SC, FC: 12 fibers ■ High density ST, SC: 24 fibers OR-615MMC-18P-00 MT-RJ, LC: 24 fibers LC quad: 48 fibers Open access, 10" x 9" x 3.5", Latching door, 5.5 lbs

OR-615SMFC-12P



Fiber Rack **Mount Cabinets** 

OR-615SMFC-12P	<ul> <li>Holds three adapter panels</li> <li>One pivoting drawer</li> <li>ST, SC, FC: 18 fibers</li> <li>LC: 36 fibers</li> <li>High density ST, SC: 36 fibers</li> <li>1 rack unit</li> </ul>
	■ 10lbs
OR-615MMC-36P-00	<ul> <li>Holds six adapter panels</li> <li>ST, SC, FC: 18 fibers</li> <li>LC: 72 fibers</li> <li>High density ST, SC: 72 fibers</li> <li>2 rack units</li> <li>15lbs</li> </ul>

OR-615MMC-18P



OR-615MMC-36P

Ada	pter	<b>Pane</b>	ls



OR-OFP-STD12MB



OR-OFP-SCD12MB OR-OFP-LCQ24MB



OR-OFP-LCD12MB

OR-OFP-BLANK	Adapter Panel, blank panel, black
OR-OFP-STS06NB	Adapter Panel, 6-ST simplex (6 fibers) multimode adapters, phosphor-bronze alignment sleeves
OR-OFP-STD12MB	Adapter Panel, 6-ST duplex (12 fibers) multi- mode adapters, phosphor-bronze alignment sleeves, beige adapters
OR-OFP-LCD12MB	6-LC duplex (12 fibers) multimode, beige adapters, phosphor-bronze alignment sleeves
OR-OFP-SCD06MB	3-SC duplex (6 fibers) multimode, beige adapters, phosphor-bronze alignment sleeves
OR OFP-SCD12MB	6-SC duplex (12 fibers) multimode, beige adapters, phosphor-bronze alignment sleeves
OR-OFP-LCQ24MB	6-LC quad (24 fibers) multimode, beige adapters, phosphor-bronze alignment sleeves



#### **Anaerobic Connectors**

OR-205KAN9GA-MM	Anaerobic Connectors, LC, multimode, buffer size (µm) 900
OR-205KAN9EA-MM	Anaerobic Connectors, ST, multimode, buffer size (µm) 900
OR-205KAN9FA-MM	Anaerobic Connectors,



OR-P1DA2BRGZGZ001M



OR-P1DA2BRFZFZ001M



OR-P1DA2BREZEZ001M

#### Duplex (2 fiber) Jumpers

#### OptiMo Multimode (62.5/125) PC/OFNR, 2mm Zip Cord

DUPLEX, LC-PC TO LC-PC	LENGTH
OR-P1DA2BRGZGZ001M	1 meter
OR-P1DA2BRGZGZ002M	2 meters
OR-P1DA2BRGZGZ003M	3 meters
DUPLEX, SC-PC TO SC-PC	LENGTH
OR-P1DA2BRFZFZ001M	1 meter
OR-P1DA2BRFZFZ002M	2 meters
OR-P1DA2BRFZFZ003M	3 meters
DUPLEX, ST-ST	LENGTH
OR-P1DA2BREZEZ001M	1 meter
OR-P1DA2BREZEZ002M	2 meters
OR-P1DA2BREZEZ003M	3 meters



OR-P1DA6BPAZAZ001M

Space Saver Fiber Optic Cable Assemblies

#### OptiMo Multimode (62.5/125) PC/OFNR (A-B)

PART NO.	LENGTH
OR-P1DA6BPAZAZ001M	1 meter
OR-P1DA6BPAZAZ002M	2 meters
OR-P1DA6BPAZAZ003M	3 meters

#### OptiMo Multimode (62.5/125) PC/OFNR (A-A)

PART NO.	LENGTH
OR-P1RA6BPAZAZ001M	1 meter
OR-P1RA6BPAZAZ002M	2 meters
OR-P1RA6BPAZAZ003M	3 meters



Swing Away Fiber Manager

PART NO.	DESCRIPTION
OR-SA-SG001	Swing Away Fiber Manager, single gang, mud ring and spool
OR-SA-DG001	Swing Away Fiber Manager, dual gang, mud ring and spool

#### Canada

570 Applewood Crescent Vaughan, Ontario L4K 4B4 905.738.9195

### designed to be better.



#### **Ortronics**

125 Eugene O'Neill Drive New London, CT 06320 800.934.5432 860.445.3900 (sales) 860.405.2992 (fax) www.ortronics.com

