



## Twist-Lock® Devices

**20 Ampere, 250 Volts**

2 Pole, 2 Wire, Non-Grounding

**Insulgrip® Plugs, Flanged Inlets, Connector Bodies and Receptacles**20A 250V  
NEMA L2-20P  
UL Listed  
2 HP**Plugs**

| Description   | Cord Dia.                 | Catalog Numbers |
|---|---------------------------|-----------------|
| Black and white nylon, polarized.<br>Multiple drive screws. | .220"-.720"<br>(5.6-18.3) | <b>HBL7102C</b> |

Accessories on page B-49.

**Flanged Inlets**

| Description  | Catalog Numbers |
|--|-----------------|
| Nylon casing, back wired, polarized.<br>Multiple drive screws. | <b>HBL8815C</b> |

Accessories on page B-48.

20A 250V  
NEMA L2-20P  
UL Listed  
2 HP**Connector Bodies**

| Description                                      | Cord Dia.                 | Catalog Numbers |
|--|---------------------------|-----------------|
| Black and white nylon.<br>Multiple drive screws. | .220"-.720"<br>(5.6-18.3) | <b>HBL7101C</b> |

Accessories on page B-49.

**Receptacles**

| Description   | Catalog Numbers |
|---|-----------------|
| Single, black phenolic.   | <b>HBL7210B</b> |
| Single, mounted on 4" (101.6)<br>round box cover, black phenolic. | <b>HBL7217B</b> |




Accessories on pages B-48 and B-49.

**Flanged Receptacles**

| Description   | Catalog Numbers |
|---|-----------------|
| Insulgrip nylon casing, back wired.<br>Multiple drive screws.               | <b>HBL8809C</b> |
| Metal flange, stainless steel casing,<br>black phenolic, exposed terminals. | <b>HBL3226</b>  |

Accessories on pages B-48 and B-49.

Notes: Only receptacles and plugs are HP rated.  
HP ratings are AC only.

**HBL7102C****HBL8815C****HBL7101C****HBL7210B****HBL8809C****HBL3226**