

Twist-Lock® Devices

20 Ampere, 250 Volts

2 Pole, 2 Wire, Non-Grounding

**Insulgrip® Plugs, Flanged Inlets,
Connector Bodies and Receptacles**

20A 250V
NEMA L2-20P
UL Listed
2 HP

Plugs

Description	Cord Dia.	Catalog Numbers
Black and white nylon, polarized. Multiple drive screws.	.220"-.720" (5.6-18.3)	HBL7102C

Accessories on page B-49.

Flanged Inlets

Description	Catalog Numbers
Nylon casing, back wired, polarized. Multiple drive screws.	HBL8815C

Accessories on page B-49.



20A 250V
NEMA L2-20P
UL Listed
2 HP

Connector Bodies

Description	Cord Dia.	Catalog Numbers
Black and white nylon. Multiple drive screws.	.220"-.720" (5.6-18.3)	HBL7101C

Accessories on page B-49.

Receptacles

Description	Catalog Numbers
Single, black phenolic.	HBL7210B
Single, mounted on 4" (101.6) round box cover, black phenolic.	HBL7217B




Accessories on pages B-48 and B-49.

Flanged Receptacles

Description	Catalog Numbers
Insulgrip nylon casing, back wired. Multiple drive screws.	HBL8809C
Metal flange, stainless steel casing, black phenolic, exposed terminals.	HBL3226

Accessories on pages B-48 and B-49.

Notes: Only receptacles and plugs are HP rated.
HP ratings are AC only.

**HBL7102C****HBL8815C****HBL7101C****HBL7210B****HBL8809C****HBL3226**

Dimensions in Inches (mm)

www.hubbell-wiring.com



Wiring Device-Kellems

B-17