

AIPHONEDB Series



Audio Door Entry You Can Count On

Easy to install and simple to use, the DB Series protects private homes and apartments. For an ideal audio door entry solution, use Aiphone's DB Series!




Hands-Free Communication in Any Place



Up to 5 Inside Stations With Room-to-Room Communication

Unable to answer your door from the Master station? No problem! Talk with visitors from anywhere in your home with up to 4 additional Sub master stations. Inside stations can be used for room-to-room communication.





Option Button

Use the Option button to control an external device, such as an entrance light.



Chime Sound


Just a press of the Call button of Door station rings the chime continuously for appropriate time (approximately 4 seconds).


2-Wire System for Simple Installation

With the easy to install two-wire system, use the DB Series to replace your door bell.



System Configuration





DB Series

Line up



DA-1DS Door station silver panel 2-Call door station



DA-2DS



DA-4DS 4-Call door station



DB-1MD Master station



DB-1SD Sub master station



PT-1211DR AC transformer *Not Available in N.A.



PT-1211C AC transformer



AC transformer *Not Available in N.A.



IER-2 Call extension



EL-12S Electric door



TAR-3 External signaling relay



AC-10S Vandal resistant access control keypad, surface mount



MCW-S/A Desk Stand for DB-1MD and DB-1SD




DAW-P Door station mounting plate (83.5mm)


PT-1211C




DBS-1AP: DB-1MD, DA-1DS, PT-1211DR *Not Available in DBS-1A: DB-1MD, DA-1DS, PT-1211C

Unit dimensions








1-1/16"

1-15/16" 1-11/16" 3-1/2" 1-1/8" IER-2 3-5/16" 4-3/4"






Features

- Two-wire system including door release
- Door release wired to door station, requiring no power transformer
- Total hands-free communication, auto-voice actuation
- Press-to-talk operation available
- User-optional function button
- Call tone MUTE with indicator
- Call extension sounder

AC-10S 3-7/8 15/16" 1-15/16"




Specifications

Power source	15V AC
AC transformer	PT-1211C
Communication	Approx. 1 min. AUTOMATIC (Hands-free); To activate, momentarily press TALK button. MANUAL (Press-to-talk/Release-to-listen); To activate, press TALK button for 1 sec. or more.
Door release	EL-12S or others (More than (AC) 70 Ω , AC 9.5 ~ 20V)
Option contact (AC/Do	C)Voltage Max.: 24V, Min.: 1V Current Max.: 1.6A, Min.: 10mA
Wiring	2 wires from AC trans to Master/Sub, Master to Door, Door to Door release 4 wires from DB-1MD to DB-1SD
Distance	Door Station ~ DB-1MD Max. 1020' (18 AWG) PT-1211C ~ DB-1MD/DB-1SD Max. 180' (18 AWG)

Caution

When existing chime wires are used, it is possible they contain AC voltage. Electric shock or unit damage could result. Ask a qualified electrician for more details.







DB-1MD ~ farthest DB-1SD Max. 330' (18AWG)

Deming Prize

Deming Medal

AIPHONE CO., LTD.

ISO 9001 ISO 9001 Certified



AIPHONE CO., LTD.



http://www.aiphone.com