




## TWIST-LOCK® Devices

**2 Pole, 3 Wire Grounding**

15 Ampere, 125, 250 Volts and 277 Volts AC

**Duplex and Single Receptacles**

Sold by:

**HBL4700****HBL4710****HBL4713****Duplex Receptacles,  
Back and Side Wired**NEMA L5-15R  
15A 125V  
UL/CSA  
0.5 HPNEMA L6-15R  
15A 250V  
UL/CSA  
1.5 HPNEMA L7-15R  
15A 277V AC  
UL/CSA  
2 HP

Description	Catalog Numbers		
Flush, brown RTP face.	<b>HBL4700*</b>	<b>HBL4550*</b>	<b>HBL4750*</b>
Flush, ivory RTP face.	<b>HBL4700I*</b>	—	—

*Fed Spec WC596***Special Purpose Duplex Receptacles  
Back and Side Wired**

Description	Catalog Numbers		
Isolated ground, flush, orange RTP face.	<b>IG4700A*</b>	<b>IG4550A*</b>	—
Corrosion resistant, yellow RTP face.	<b>HBL47CM00*</b>	—	—

*Fed Spec WC596***Single Receptacle,  
Back and Side Wired**

Description	Catalog Numbers		
Flush, black nylon face.	<b>HBL4710</b>	<b>HBL4560</b>	<b>HBL4760</b>

**Special Purpose Single Receptacles,  
Back and Side Wired**

Description	Catalog Numbers		
Isolated ground, flush, orange nylon face.	<b>IG4710</b>	<b>IG4560</b>	
Single, black nylon face mounted on a 4" (101.6) round box cover.	<b>HBL4711</b>	—	<b>HBL4761</b>
Panel mount, black nylon face, side wired only, 1.75" or 1.937" (44.5 or 49.2) mounting centers.	<b>HBL4713</b>	<b>HBL4563</b>	<b>HBL4763</b>

*Notes: HP ratings are AC only.**RTP is an abbreviation for reinforced thermoplastic polyester.**See Section J for full line of isolated ground devices.**See pages B-66 and B-67 for accessories.**\*Supplied with break-off tabs for split circuit wiring.*