

ACCESSORIES

**Bottom Panel Kit**

The Bottom Panel Kit covers the bottom of the T-Series SteelFrame Cabinet to block airflow into and out of the base of the cabinet. Use with an Air Dam Kit and Snap-In Filler Panels to enhance front-to-rear or front-to-top airflow through cabinets when cabinets are supported on leveling feet or casters.

- Seals the base of 39" (990 mm) and 44"D (1120 mm) T-Series SteelFrame Cabinets manufactured after May 2009
- Includes one brush-sealed, 3" x 11.5" (76 mm x 292 mm) cable access port located at the rear center of the panel
- A CPI Passive Cooling Solution

Part Number	Description	Shipping Weight
14274-X01	For T1 x 44"D (1120 mm)	17 lb (7.7 kg)
14274-X02	For T2 x 44"D (1120 mm)	19 lb (8.6 kg)
14274-X03	For T1 x 39"D (990 mm)	15 lb (6.8 kg)
14274-X04	For T2 x 39"D (990 mm)	17 lb (7.7 kg)

X=color: 1=Gray, 2=Computer White, 7=Black

**Airflow Director**

Directs hot exhaust air from the bottom part of the cabinet to the top of the cabinet. Use with the high-density T-Series SteelFrame Cabinet with Vertical Exhaust Duct, an Air Dam Kit and Snap-In Filler Panels to create one-way, front-to-top airflow through the cabinet.

- 9.9"H x 8.0"D (252 mm x 203 mm)
- Attaches to the cabinet frame; match to cabinet width: T1 or T2
- A CPI Passive Cooling Solution

Part Number	Description	Shipping Weight
14272-X01	Airflow Director Kit for T1	5 lb (2.3 kg)
14272-X02	Airflow Director Kit for T2	5 lb (2.3 kg)

X=color: 1=Gray, 2=Computer White, 7=Black

**Air Dam Kit**

Blocks airflow between equipment mounting rails and the top, bottom and sides of the cabinet's frame, routes chilled air through the equipment and prevents hot exhaust air from re-circulating inside the cabinet space. Use with Snap-In Filler Panels and the Bottom Panel Kit to create one-way airflow through the cabinet.

- 5"D (130 mm) baffles
- Attaches to the cabinet frame; match to cabinet height
- A CPI Passive Cooling Solution

Part Number	Description	Shipping Weight
13338-X10	For 45 RMU, 84"H (2130 mm)	11 lb (5.0 kg)
13338-X11	For 42 RMU, 78"H (1980 mm)	10 lb (4.5 kg)

X=color: 1=Gray, 2=Computer White, 7=Black

**Narrow Vertical Cable Manager**

Vertical cable manager for T1-style T-Series SteelFrame Cabinets. Attaches to the cabinet frame in the space between the equipment mounting rails and the side panel.

- Slides front-to-rear, independent of the equipment mounting rails
- Includes eight .9"W x 3.3"D (20 mm x 84 mm), plastic, C-shaped cable rings
- Cable rings snap onto the mounting bracket and can be oriented with the side or the front/rear of the cabinet

Part Number	Description	Shipping Weight
11809-X00	For 45 RMU, 84"H (2130 mm), T1	5 lb (2.3 kg)
11809-X01	For 42 RMU, 78"H (1980 mm), T1	5 lb (2.3 kg)

X=mounting bracket color: 1=Gray, 2=Computer White, 7=Black. Rings are black plastic.

**Caster Kit**

Castors make it easy to move the cabinet to quickly reconfigure your work space.

- Front casters swivel; rear casters are fixed
- Increases cabinet height by 4.28" (105 mm)
- Attaches to the bottom of the cabinet frame; install casters prior to populating the cabinet

**Caster Kit includes:**

- Two gussets with locking full-swivel casters (front)
- Two reinforcement plates and fixed casters (rear)
- Installation hardware

Part Number	Description	Shipping Weight
14275-001	Caster Kit for T-Series	25 lb (11.3 kg)

**Fan Kit**

Forces hot exhaust air out of the top of the standard cabinet.

- Provides up to 300 CFM of ventilation for the cabinet
- Quick, easy mounting to the inside of the top panel on standard cabinets (not for use on high-density cabinets that have a Vertical Exhaust Duct)
- Includes one 12'L (3.7 m), detachable power cord with IEC C-13 connector and molded plug
- UL Recognized

Part Number	Description	Shipping Weight
12724-701	115 VAC, 50/60 Hz, NEMA 5-15P Plug	8 lb (3.6 kg)
12724-702	230 VAC, 50/60 Hz, NEMA 6-15P Plug	8 lb (3.6 kg)

Color is Black.

**Intelligent Fan Door**

Pushes hot exhaust air out of the rear of the standard cabinet.

- Temperature-controlled, variable speed DC fans provide up to 960 CFM of ventilation for the cabinet
- Quick, easy attachment; includes a push-button lock keyed to match cabinet doors/side panels
- Includes two 10'L (3 m), detachable power cords, each with (1) IEC C-13 connector and a molded NEMA 5-15P plug; requires two 115 VAC, 60 Hz power connections

Part Number	Description	Shipping Weight
13214-X10	For 45 RMU, 84"H (2130 mm), T1	66 lb (29.9 kg)
13214-X11	For 42 RMU, 78"H (1980 mm), T1	63 lb (28.6 kg)
13214-X20	For 45 RMU, 84"H (2130 mm), T2	71 lb (32.2 kg)
13214-X21	For 42 RMU, 78"H (1980 mm), T2	68 lb (30.8 kg)

X=color: 1=Gray, 2=Computer White, 7=Black

**Vertical Cable Manager**

Vertical cable manager for T2-style T-Series SteelFrame Cabinets. Attaches to the cabinet frame in the space between the equipment mounting rails and the side panel.

- Slides front-to-rear, independent of the equipment mounting rails
- Includes eight 2.3"W x 5.5"D (58 mm x 140 mm), plastic, C-shaped cable rings
- Cable rings and bracket can be oriented with the side or the front/rear of the cabinet

Part Number	Description	Shipping Weight
12465-X07	For 45 RMU, 84"H (2130 mm), T2	7 lb (3.2 kg)
12465-X06	For 42 RMU, 78"H (1980 mm), T2	7 lb (3.2 kg)

X=mounting bracket color: 1=Gray, 2=Computer White, 7=Black. Rings are black plastic.

