

Clarity 5E 12-port, Category 5e mini patch on 89D bracket, 10" x 2.3" - OR-PMP5E1289



Clarity 5E 12-Port Mini Patch Panel is component compliant to EIA/TIA Category 5e performance requirements. Its high density design on a supplied 89D bracket maximizes wall space in small or confined locations. The panel measures 10" x 2.5". Jacks are grouped in six-port modules. Part of the Clarity 5E link and channel solution that provides significant installed performance headroom.



FEATURES

- **ETL verified to TIA Category 5e component spec:** Elevated component performance.
- **Center tuned to Clarity 5E patch cords:** More transparent mated union.
- **Universal wiring:** Supports T568A and T568B installs.
- **Easy lace 110 termination:** Saves installation time.
- **Supplied rear cable management:** Supports good cabling practice.
- **High density design:** Maximizes rack utilization.
- **RoHS compliant:** Lead free.

Specifications

DIMENSION INFO

Height Metric: 254 mm

Width Metric: 58.42 mm

Cable Diameter Range: 22-26 AWG

Height U S: 10 in

GENERAL INFO

Mod Jack Wiring: Universal T568A/B

Number Of Ports: 12

TECHNICAL INFO

Performance Rating: Category 5e

Category Rating: Category 5e

CONSTRUCTION INFO

Component1: Panel - Material1: 0.125" Aluminum, Finish_Plating1: Painted black texture with green silkscreen

Component4: Array of eight modular dual reactance contacts - Material4: Beryllium copper, Finish_Plating4: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Component5: IDC contacts (low noise) - Material5: Phosphor Bronze, Finish_Plating5: Nickel plating with tin over plate

LISTING AGENCY INFO

FCC

UL E131600

BUY AMERICAN ACT COMPLIANCE

Country of Origin: UNITED STATES OF AMERICA

Buy American Act Status: Buy American Act Compliant