

Ortronics OR-PHAPJU48

Rear load angled high density jack panel kit for 48 Clarity 6 or 5E panel jacks - OR-PHAPJU48

Rear load angled high density jack panel kit for 48 Clarity 6 or 5E panel jacks. It occupies 2 rack units and measures 19" x 3.5".





FEATURES

- Jacks rear load into panels: All terminations done from rear of panel.
- New positive jack latching design: Secure mounting of jacks into panel.
- Recessed design with lower mounted profile: Directs cords more easily to vertical management.
- High density solution: Maximizes rack space.
- Panel jacks support snap-in icons: Easy designation of ports.
- Universal wiring labels on panel jacks: Supports both T568B and T568A wiring schemes.
- Silkscreened 1-48: Easy port identification.

Specifications





Ortronics OR-PHAPJU48

APP INSTALL INFO

Mounting Hardware Included: Yes

Installation Tips: Terminate panel jack and then rear load into the panel, maintaining minimum bend radius of four times

the cable diameter.

DIMENSION INFO

Height Metric: 88.90 mm Width Metric: 482.6 mm Depth Metric: 38.86 mm

Height US: 3.5 in

GENERAL INFO

Category Performance Application: Category 6 or 5e when loaded with Category 6 or 5e panel jacks

Mod Jack Wiring: Field defined Number Of Ports: Up to 48 Color: Black with blue silkscreen

Footprint: Clarity 6 or 5E rear load PJ series panel jacks

TECHNICAL INFO

Performance Rating: Category 6 or 5e, based on selection of panel jack

CONSTRUCTION INFO

Component1: Panel - Material1: .090 aluminum, Finish_Plating1: Black with blue silkscreen

Component2: Patch Panel Mounting Screws #12-24 x 5/8" - Material2: Steel, Finish_Plating2: Black

LISTING AGENCY INFO

UL E131600

BUY AMERICAN ACT COMPLIANCE

Country of Origin: UNITED STATES OF AMERICA Buy American Act Status: Buy American Act Compliant

