
12 Fiber Singlemode SC-Duplex MPO Cassette

PRODUCT SPECIFICATION




Features and Benefits:


- High quality aluminum material allows for compact and durable cassettes.
- Cassette offers a plug and play solution which saves assembly and termination time.
- Designed to fit ICC's wall mount enclosures (ICFOD) and rack mount enclosures (ICFOR).
- MPO connector reduces insertion loss which enhances channel link performance.
- Suitable for any applications with a need for higer bandwidth with longer distances.
- Cassette allows up to 36 fibers within 1 RMS.
- Available in black.

| МРО | CASSETTE, 1 | 2F, SM, SC | , DUP, 9 | μm |
|----------|-------------|------------|----------|----|
| ITEM NO. | ICFC12SSD9 | | REV. A | |
| DWG NO. | PSFC12SSD9 | | PAGE NO. | 1 |



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com





NOTE: UNLESS OTHERWISE SPECIFIED

1. CASSETTE HOUSING:

A. MATERIAL: ALUMINUM ALLOY

B. SURFACE FINISHING: BLACK POWDER COAT

2. SC-DUPLEX CONNECTOR:

A. MATERIAL: ABS
B. COLOR: BLUE
C. SLEEVE: CERAMIC

D. INSERTION LOSS: <=0.3 dB (1300nm) E. OPERATING TEMPERATURE: -20° ~ 70° F. STORAGE TEMPERATURE: -40° ~ 80°

3. MPO ADAPTER:

A MATERIAL: (PBT)

B. INSERTION LOSS: <0.5dB (1310nm)

C. COLOR: GREEN

D. MATING CYCLES: 1000 MATING CYCLES

E. DUST CAP: TPR COLOR: BLACK 4. FIBER TYPE: 9/125µm



| MPO C | ASSETTE, 12F, S | SM, SC, DUP, 9 μm |
|----------|-----------------|-------------------|
| ITEM NO. | ICFC12SSD9 | REV. A |
| DWG NO. | PSFC12SSD9 | PAGE NO. 2 |



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com