

Product Datasheet

Catalog Home

Home Page

Search

IG4560 -- Isolated Ground Twist-Lock Receptacle



IG4710

2P3W, 15A 250V, L6-15R, IG, Single, Orange Nylon Face

Product Specifications

Product Type	<p>Twist-Lock Devices</p>
Product Item	Single Receptacle
Wiring Scheme	2-Pole, 3-Wire Grounding
Amperage	15A
Voltage	250V AC
NEMA Configuration	L6-15R
Item Style	Isolated Ground
Device Color	Orange
Horsepower	0.5
Terminal Clamp Material	.062" (1.6) Steel
Terminal Screw Material	#8-32 Brass
Ground Screw Material	#8-32 Brass (Green)
Contact Spring Material	.031" Brass
Mounting Screw Material	Steel-zinc-plated
Cover (Top) Material	Black Nylon
Base Material	Black Rynite
Ground Contact Material	.031" Brass
Bridge (Mounting Strap) Material	.050" Steel-zinc-plated
Rivet Material	Brass
Auto Ground Clip Material	Stainless Steel
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Terminal Accommodation	20A #12 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors.

Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Listings	UL/CSA
Catalog Page	Click here for catalog page B11
Brochures	Click here for product brochure
Catalog Section	Click here for Section-B
UPC Number	78358577993
Weight in LBs	0.15

