

Product Datasheet

Catalog Home

Home Page

Search

HBL4723VY -- Twist-Lock Valise Plug



2P3W, 15A 125V, L5-15P, Yellow Nylon

HBL4723VY

Product Specifications

Product Type	 Twist-Lock Devices
Product Item	Plug
Wiring Scheme	2-Pole, 3-Wire Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	L5-15P
Item Style	Valise
Device Color	Yellow
Horsepower	0.5
Cord Dia.	.220"-.660" (5.6-16.8)
Blade Holder Material	yellow nylon
Housing Material	Yellow nylon
Cord Clamp Material	Phenylene-oxide (NORYL)
Blade Material	Brass
Terminal Clamp Material	Cold rolled steel-nickel-plated
Terminal Screw Material	#8-32 Steel (copper flash, nickel plate & molykote)
Ground Screw Material	Steel (green finish)
Cord Clamp Screw Material	Steel-zinc-plated
Body Holding Screw Material	Steel-zinc-plated
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	15A #14 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20

Listings	UL/CSA
M Drawings	Click here for M-Drawing
Catalog Page	Click here for catalog page B10
Catalog Section	Click here for Section-B
UPC Number	783585236803
Weight in LBs	0.15

