

You are here: [Home](#) > [Products](#) > [Surge Protection and Power Conditioning](#) > [Surge Protection Devices](#) > [SurgeArrest Performance](#)




APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V

Part Number: P11VNT3



[Technical Specifications](#) [Product Overview](#) [Documentation](#) [Ratings and Reviews](#)

| Output | |
|---|--|
| Number of Outlets | 11 |
| Receptacle Style | NEMA 5-15R |
| Input | |
| Nominal Input Voltage | 120V |
| Input Frequency | 50/60 Hz |
| Input Connections | NEMA 5-15P  |
| Cord Length | 8 feet (2.44 meters) |
| Input Breaker Capacity | 15.0 A |
| Surge Protection and Filtering | |
| Surge energy rating | 3020 Joules |
| EMI/RFI Noise rejection (100 kHz to 10 MHz) 70 dB | |
| Data Line Protection | Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Network line - 10/100 Base-T Ethernet (RJ-45 connector), Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector) |
| Let Through Voltage Rating | < 40 |
| Physical | |
| Net Weight | 2.33 lbs. (1.06 kg) |
| Maximum Height | 1.57 inches (40 mm) |

| | |
|---|---|
| Maximum Width | 4.70 inches (119 mm) |
| Maximum Depth | 11.89 inches (302 mm) |
| Shipping Weight | 2.97 lbs. (1.35 kg) |
| Shipping Height | 2.36 inches (60 mm) |
| Shipping Width | 7.56 inches (192 mm) |
| Shipping Depth | 13.58 inches (345 mm) |
| Master Carton Units | 6.00 |
| Master Carton Dimensions (Length x Width x Height) | 15 x 8 x 15 inches (378 x 210 x 377 mm) |
| Master Carton Weight | 19.58 lbs. (8.90 kg) |
| SCC Codes | 1073130424902 0 |
| Color | Black |
| Environmental | |
| Operating Environment | 32 - 113 °F (0 - 45 °C) |
| Operating Relative Humidity | 0 - 95% |
| Operating Elevation | 0-10000 feet (0-3000 meters) |
| Storage Temperature | 5 - 113 °F (-15 - 45 °C) |
| Storage Relative Humidity | 0 - 95% |
| Storage Elevation | 0-50000 feet (0-15000 meters) |
| Conformance | |
| Regulatory Approvals | CSA,NOM,UL 1363,UL 1449 |
| Standard Warranty | Lifetime |
| Equipment protection policy | Lifetime : \$100000 |
| UL 1449 TVSS Rating | 330V |

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.