

Product Datasheet

Catalog Home

Home Page

Search

HBL2325SW -- Twist-Lock Watertight Safety-Shroud Flanged Inlet



2P3W, 20A 250V, L6-20P, Gray Thermoplastic Polyester

Product Specifications

Product Type	 Twist-Lock Devices
Product Item	Flanged Inlet
Wiring Scheme	2-Pole, 3-Wire Grounding
Amperage	20A
Voltage	250V AC
NEMA Configuration	L6-20P
Item Style	Shrouded Watertight
Device Color	Gray
Terminal Retainer Material	Clear polycarbonate
Blade Material	Brass
Terminal Clamp Material	.08" (2) steel-nickel plated
Terminal Screw Material	#10-32 Brass (white finish on neutral screw when used) Multi-drive
Ground Screw Material	#10-32 Brass (green finish) Multi-drive
Body Holding Screw Material	Stainless steel, Multi-drive
Body Contact Carrier Material	Natural White Nylon
Flanged Casing Material	Gray Valox
Mounting Screw Material	Stainless Steel 302/304 Multi-drive
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Terminal Accommodation	20A #12 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	VO per UL94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	Type 4, 4X, 12, IP66 suitability

Closure Cap and Strap Material	Neoprene EPDM Blend
Listings	FED SPEC UL/CSA
Catalog Page	Click here for catalog page B18
Brochures	Click here for product brochure
Catalog Section	Click here for Section-B
UPC Number	783585231143
Weight in LBs	0.6

