

CHAT[®] 160 | **CHATAttach**[™] 160

Personal/Group Speakerphones for Skype[™]



Speakerphones for individual, small, medium and large group use, the CHAT 160 and CHATAttach 160 connect to PCs and laptops for rich, hands-free calls with Skype. The CHAT 160 and CHATAttach 160 are completely full-duplex, contain HDConference[®] and are the perfect addition to the office or conference room for greatly enhanced collaboration.



APPLICATIONS

Perfect for:

- + Small, medium and large Conference Rooms
- + The Office
- + SOHO

Skype:

- + Incoming calls ring on the CHAT 160 and
- CHATAttach 160 + No headset wires or
- discomfort
- + Plug-and-play operation

Other devices or applications:

- + Internet phone applications
- + Instant messaging
- applications
- + VoIP softphones
- + Enterprise telephones
- + Web conferencing
- + Audio playback
- + Desktop video conferencing

DELIVERS

SUPERIOR

HANDS-FREE

SKYPE CALLS

AUDIO FOR

ADVANTAGES

Provides high quality speakerphone capabilities on PCs or laptops:

- + Connect the CHAT 160 or the CHAT Attach 160 to PCs and laptops via USB for hands-free, full-duplex audio with Skype
- + Hands-free flexibility and comfort:
 - > Move around freely without being tethered with a headset
 - > Avoid discomfort caused by prolonged headset use
 - > Easily includes groups of participants on Skype calls
- + Replaces the PC's speakers and microphone with a high-quality, full-duplex audio solution
- + True plug-and-play operation
- + Crystal-clear audio for video conferencing and streamed multimedia content
- + Sleek industrial design complements the professional environment of any office or meeting room

Enjoy crisp, clear audio:

- + Advanced HDConference audio processing technologies deliver remarkably rich, full audio for natural, effortless conversations:
 - > True full-duplex performance allows users to listen and speak at the same time without audio cutting in and out
 - > Distributed Echo Cancellation® eliminates acoustic echo
 - > Noise reduction identifies and removes ambient room noise
 - > First mic priority turns down the microphones that are not in use
 - > Advanced automatic level management automatically adjusts microphone levels
- + Three built-in microphones provide full 360-degree coverage up to 8 feet from the speakerphone
 - > Easily manage audio for 1-6 call participants
 - > Provides rich audio from the far side participants
- + Full bandwidth frequency response delivers better audio

ClearOne

CHAT 160 COMPONENTS

CHATAttach COMPONENTS

CHATAttach Packout for the CHAT 160

CHATAttach Expansion Cable Packout



Part # 910-156-251

USB 2.0 Connection Cable Part # 830-156-200

Quick Start Guide Part # 800-156-251

Two CHAT 160 Units Part # 910-156-251

CHATAttach Cable

Part # 830-156-010L

6 USB 2.0 Connection Cable Part # 830-156-200

CHATAttach

Power Supply

Part # 551-156-200

CHATAttach Cable Part # 830-156-010L

CHATAttach

Quick Start Guide

Part # 800-156-225





Quick Start Guide Part # 800-156-225

Ready to use out of the box

All the components you need to quickly get up and running, including cabling and Quick Start Guide.

ROOM APPLICATIONS





CHATAttach 160

Device Setup My Devices Help

Configuration Software

Allows users to easily switch between devices; software applies optimized settings to CHAT 160 for each device. Auto-updates from the Web to keep software & CHAT 160 up-to-date with the latest enhancements.

SPECIFICATIONS

System Requirements Windows XP, Windows Vista or Windows 7

Connections USB:

Version 2.0 Compatible Type: Mini-B Female

Keyed Connector: Keyed RJ-45 (8-conductor)

Controls Volume Up Volume Down Microphone Mute

Audio Speaker: Bandwidth: 190 Hz - 20 kHz

Max Output Level: 85 dB SPL @ 1 foot (0.30 meter)

Microphone Bandwidth: 50 Hz - 7.75 kHz

Environmental Operating Temperature: 41 - 104° F (5 - 40° C)

Processing Full Duplex

Distributed Echo Cancellation (D.E.C.)® Noise Cancellation (NC) Automatic Level Control (ALC) Line Echo Cancellation (LEC) - Selectable First Mic Priority

Power USB:

5 VDC @ 500 mA Maximum

External:

Input: 100 - 240 VAC Output: 9 VDC @ 560 mA

Tip: Power Ring: Ground

Mechanical

Dimensions ($W \times D \times H$): 7.4" x 7.4" x 1.8" (18.8 cm x 18.8 cm x 4.6 cm)

Weight: 1.17 lbs (0.53 kg)

RoHS REACH FCC Class A Part 15 ICES-003 CE Listed **UL** Listed

Compliance

Model Numbers

CHATAttach

910-156-251 CHAT 160

• Single CHAT 160 and Connecting Cable

910-156-251-00 CHATAttach 160

• Two (2) CHAT 160 Devices, Connecting Cables and Power Supply

Accessory Part Numbers 910-156-225 CHATAttach Expansion Kit

• Includes Cables, Power Supply and Quick Start Guide to Update Two (2) CHAT 160 Devices to

CLEARONE LOCATIONS

HEADQUARTERS:

Salt Lake City, UT USA 5225 Wiley Post Way Suite 500 Salt Lake City, UT 84116

Tel: 801-975-7200 Toll Free: 800-945-7730 Fax: 801-977-0087 E-mail: sales@clearone.com Latin America Tel: 801-974-3621 E-mail: global@clearone.com **FMFA** Tel: 44 (0) 1189 036 053 E-mail: global@clearone.com APAC Tel: 801-303-3388 E-mail: global@clearone.com Technical Support Tel: 800.283.5936 E-mail: Tech.Support@ClearOne.com

*Other product names may be registered trademarks of their respective owners who do not necessarily endorse ClearOne or ClearOne's products All rights reserved. Information in this document subject to change without notice. © 2010 ClearOne Communications Inc. 802-156-251-DS Revision 2.2 October 2010