

Supports (continued from page 3)

**Center Support Bracket**

- Use to support wire mesh cable tray from the ceiling with a single 3/8" (M10) or smaller threaded rod and hardware (sold separately)
- Tray attaches to the Center Support Bracket with two splice washers from the Splice Washer & Bolt Kit (P/N 34728-X01) or use fold-over tabs to secure the tray on all sizes except the 4"W (100 mm) version
- Used to support a single cable tray
- Manufactured from steel
- Sold individually

Part Number & Finish		Description Width in - (mm)	Shipping Weight lb (kg)
Zinc	Black		
34729-504	34729-704	For 4 (100) Tray	1 (0.5)
34729-508	34729-708	For 8 (200) Tray	1 (0.5)
34729-512	34729-712	For 12 (300) Tray	2 (0.9)
34729-516	34729-716	For 16 (400) Tray	2 (0.9)
34729-520	34729-720	For 20 (500) Tray	2 (0.9)
34729-524	34729-724	For 24 (600) Tray	3 (1.4)

**C Support Bracket**

- Use to support wire mesh cable tray against the wall and ceiling
- Allows easy side access to cables within the tray
- Installation requires 1/4" (M6) hardware (order separately)
- Tray attaches to the C Support Bracket with two splice washers from the Splice Washer & Bolt Kit (P/N 34728-X01)
- Manufactured from steel
- Sold individually

Part Number & Finish		Description Width in - (mm)	Shipping Weight lb (kg)
Pre-Galv	Black		
34134-604	34134-704	For 4 (100) Tray	3 (1.4)
34134-608	34134-708	For 8 (200) Tray	3 (1.4)
34134-612	34134-712	For 12 (300) Tray	3 (1.4)
34134-618	34134-718	For 18 (450) Tray	4 (1.8)

**L Support Bracket**

- Use to support a wire mesh cable tray pathway along a wall or under a floor
- Installation requires 1/4" (M6) hardware (ordered separately)
- Use the 16"W (400 mm) or smaller version to support cable tray from an access floor pedestal; attach to the pedestal with a single Pedestal Clamp Bracket (P/N 34737-501); floor height must be at least 12" (300 mm)
- Tray attaches to the L Support Bracket with two splice washers from the Splice Washer & Bolt Kit (P/N 34728-X01) or use the fold-over tab at the end of the bracket to secure the tray
- Can be used to support multiple trays of varying widths; the combined width of multiple trays must not exceed the width of the tray stated in the order table below
- Manufactured from steel
- Sold individually

Part Number & Finish			Description Width in - (mm)	Shipping Weight lb (kg)
Zinc	Pre-Galv	Black		
34734-504	34734-604	34734-704	For 4 (100) Tray	1 (0.5)
34734-508	34734-608	34734-708	For 8 (200) Tray	2 (0.9)
34734-512	34734-612	34734-712	For 12 (300) Tray	2 (0.9)
34734-516	34734-616	34734-716	For 16 (400) Tray	3 (1.4)
34734-520	34734-620	34734-720	For 20 (500) Tray	3 (1.4)
34734-524	34734-624	34734-724	For 24 (600) Tray	4 (1.8)

Note: Use 8"W (200 mm) L Support Bracket for 6"W (150 mm) trays; use 20"W (500 mm) bracket for 18"W (450 mm) tray.

**Triangle Support Bracket**

- Use to support a wire mesh cable tray pathway along a wall
- Installation requires 3/8" (M10) hardware (ordered separately)
- Tray attaches to the Triangle Support Bracket with two splice washers from the Splice Washer & Bolt Kit (P/N 34728-X01) or use the fold-over tab at the end of the bracket to secure the tray
- Manufactured from steel
- Sold individually

Part Number & Finish			Description Width in - (mm)	Shipping Weight lb (kg)
Zinc	Pre-Galv	Black		
34733-504	34733-604	34733-704	For 4 (100) Tray	1 (0.5)
34733-508	34733-608	34733-708	For 8 (200) Tray	1 (0.5)
34733-512	34733-612	34733-712	For 12 (300) Tray	2 (0.9)
34733-516	34733-616	34733-716	For 16 (400) Tray	3 (1.4)
34733-520	34733-620	34733-720	For 20 (500) Tray	3 (1.4)
34733-524	34733-624	34733-724	For 24 (600) Tray	4 (1.8)

Note: Use 8"W (200 mm) Triangle Support Bracket for 6"W (150 mm) trays; use 20"W (500 mm) bracket for 18"W (450 mm) tray.

**Under Floor C Bracket**

- Use to support two tiers of wire mesh cable tray under a raised access floor
- Allows easy side access to cables within the tray
- Attach to a floor pedestal with a Pedestal Clamp Bracket (P/N 34737-501)
- Tray attaches to the Under Floor C Bracket with two splice washers from the Splice Washer & Bolt Kit (P/N 34728-X01)
- Manufactured from steel, 7.8"H (198 mm)
- Sold individually

Part Number & Finish		Description Width in - (mm)	Shipping Weight lb (kg)
Pre-Galv	Black		
34140-606	34140-706	For 6 (150) Tray	3 (1.4)
34140-612	34140-712	For 12 (300) Tray	5 (2.3)

**Trapeze Support Bracket**

- Use to support wire mesh cable tray from the ceiling using a pair of threaded rods
- Installation requires a pair 1/2"(M13) or smaller threaded rods and hardware (order separately)
- Tray attaches to the Trapeze Support Bracket with two splice washers from the Splice Washer & Bolt Kit (P/N 34728-X01)
- Can be used to support multiple trays of varying widths; the combined width of multiple trays must not exceed the width of the tray stated in the order table below
- Manufactured from steel
- Sold individually

Part Number & Finish			Description Width in - (mm)	Shipping Weight lb (kg)
Zinc	Pre-Galv	Black		
34730-512	34730-612	34730-712	For 12 (300) Tray	2 (0.9)
34730-516	34730-616	34730-716	For 16 (400) Tray	2 (0.9)
34730-520	34730-620	34730-720	For 20 (500) Tray	3 (1.4)
34730-524	34730-624	34730-724	For 24 (600) Tray	3 (1.4)