

FDC® Unit Connector Module, pigtailed, ST® Compatible Connectors

MIC® Tight-Buffered Cable, 3 m, 12 F, Single-mode (OS2)

CORNING

Corning Cable Systems offers a variety of panels and modules for use in the FDC® unit family of products. The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly to the FDC unit housing. Both the panels and the modules may be equipped with 900 µm single-fiber or ribbon-fiber pigtails for pigtail splicing. Panels and modules are available with a variety of connector types. Plastic modules include molded-in areas for coiling fiber slack and protecting the minimum bend-radius of the fiber.

Features and Benefits

Compatible with Corning Cable Systems Fiber Distribution Centers (FDC®)

Reduced inventory complexity

Termination of interbuilding backbone cables at main or intermediate cross-connect

Variety of deployment options

Modules accommodate various fiber and connector types

Flexibility of deployment

Fiber routing and bend-radius protection designed into modules

Clean and easily accessible fiber routing with fewer breaks

Specifications

General Specifications	
Application	Central Office, Carrier Networks, Enterprise Networks
Product Type	Panels & Modules
Fiber Category	Single-mode (OS2)
Cable Type Stubbed	MIC® Cable subunit

FDC® Unit Connector Module, pigtailed, ST® Compatible Connectors

MIC® Tight-Buffered Cable, 3 m, 12 F, Single-mode (OS2)

CORNING

Design - Hardware

Connector Type A	ST® Compatible
Connector Polish	UPC
Fiber Count	12
Number of Adapters per Panel	12
Pigtail Length	9.84 ft (3 m)

Design Adapter

Adapter Housing Color	Blue
Adapter Housing Material	Composite
Adapter Style	Standard
Adapter Type	ST® Compatible
Insert Material	Ceramic

Ordering Information

Order Number	FDM12P12-19-3RH000
Product Description	FDC® Unit Connector Module, pigtailed, ST® Compatible Connectors, MIC® Tight-Buffered Cable, 3 m, 12 F, Single-mode (OS2)

Shipping Information

Units per Delivery	1/1
Package Contents	FDC® Unit Connector Module, Pigtailed, 12 F, ST® Compatible Connectors, MIC® Tight-Buffered Cable, Single-mode (OS2), 3 m

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

CORNING