

SERIES II® Modules

NOTE: All Ortronics product dimensions are listed by width, height and depth unless specified otherwise.
Ortronics® Clarity® Series II modules combine the improved performance of center tuned Category 6 or 5e connector technology with the ease and reliability of rugged, front-loading Series II modules with linear 110 termination.



Clarity 6 and Clarity 5E Enhanced Category 6 and 5e Series II Modules



PART NO.	DESCRIPTION
OR-S21600	Single enhanced Category 6 jack, 8-position, 180° exit, universal T568A/B wiring
OR-S22600	Dual enhanced Category 6 jack, 8-position, 180° exit, universal T568A/B wiring
OR-S215E00	Single enhanced Category 5e jack, 8-position, 180° exit, universal T568A/B wiring
OR-S225E00	Dual enhanced Category 5e jack, 8-position, 180° exit, universal T568A/B wiring

NOTE: Clarity Series II modules are available in -99 Wiremold® ivory, -88 white and -00 black. Icon compatible.

Additional Series II Jack Modules



PART NO.	DESCRIPTION
OR-S21RJ61	Single USOC RJ61 jack, 8-position, 180° exit
OR-S22RJ61	Dual USOC RJ61X jack, 8-position, 180° exit
OR-S22RJ25-5E	Single RJ25 USOC 6-position jack, single T568A/B Category 5e, 8-position jack, 180° exit
OR-S21RJ25	Single USOC RJ25 jack, 6-position, 180° exit
OR-S22RJ25	Dual USOC RJ25 jack, 6-position, 180° exit

NOTE: See page 194 for Fiber Series II modules