

# AISLELOK™ ACRYCELL™ SEALING TAPE

## KEY FEATURES

- Expands to fill and seal gaps between cabinets or other surfaces
- Easy peel and stick installation uses adhesive to secure tape directly to the surface
- Will remain securely attached in high temperature environments
- Durable, flexible non-particulating sealing material

## APPLICATIONS

- Seal openings between and under adjacent cabinets or surfaces to help prevent bypass airflow around or under the cabinet.

## USE WITH

- CPI Cabinet and Enclosure Systems

## RELATED ACCESSORIES

- HotLok® Snap-In Filler Panels
- Air Dam Kit
- Bottom Panel
- Vertical Exhaust Duct System
- Aisle Containment
- AisleLok™ Under Rack Panel
- KoldLok® Raised Floor Grommet

NEW!



**AisleLok Acrycell  
Sealing Tape**

Available in three sizes

Separating hot and cold air within the data center computer room is the key to maximizing cooling system efficiency. The standard practice of aisle containment is one of the easiest ways to reach those efficiencies, but it will not completely prevent the mixing of hot and cold air. An optimized aisle containment solution also requires sealing the gaps between and under each cabinet in the data center.

AisleLok Acrycell Sealing Tape seals the gaps between and under cabinets, ensuring that hot and cold air in the data center remain completely separated. AisleLok Acrycell Sealing Tape has a strong adhesive backing that features easy “peel and stick” installation and will remain securely attached in high temperature environments. The tape also features time release expansion to ensure a tight seal between cabinets or other surfaces, is data center safe, non-particulating and RoHS compliant.

See reverse for product selection. Contact CPI Technical Support for configuration assistance.



CHATSWORTH PRODUCTS, INC.

**+1-800-834-4969**

techsupport@chatsworth.com  
www.chatsworth.com


## SPECIFICATIONS

- AisleLok Acrycell Sealing Tape blocks airflow between and under cabinets and other surfaces when cabinets are arranged into a continuous row or when a cabinet is placed in a standalone application
- For indoor use only, in environmentally controlled areas, may not be used outdoors or in harsh environments
- Available in three sizes, see Dimensions Table
- Expands in thickness to fill gap, see Ordering Information Table
- Non-particulating
- 2002/95/EC, RoHS compliant
- Durable adhesive backing
- Temperature resistant from -40°F to 212°F (-40°C to 100°C)
- Fire resistant to DIN 4102 Class B1
- Black finish

## ORDERING INFORMATION

AisleLok™ Acrycell™ Sealing Tape		
Part Number	Description	Shipping Weight lb (kg)
13876-000	.5" Sealing Tape Expands to seal gaps between .20" (5 mm) and .50" (12.7 mm) wide, Pack of 5, Black	3 (1.4)
13876-001	1" Sealing Tape Expands to seal gaps between .47" (12mm) and 1.0" (25.4 mm) wide, Pack of 5, Black	5 (2.3)
13876-002	2" Sealing Tape Expands to seal gaps between .87" (22 mm) and 2.0" (50.8 mm) wide, Pack of 5, Black	7 (3.2)


*Note: See Dimensions for more details.*



## DIMENSIONS

Part Number	Description	Tape Width in (mm)	Roll Length in (m)	Min. Thickness in (mm)	Max. Thickness in (mm)
13876-000	.5" Sealing Tape	.39 (10)	32.8 (10)	.20 (5)	.50 (12.7)
13876-001	1" Sealing Tape	.59 (15)	18.4 (5.6)	.47 (12)	1.0 (25.4)
13876-002	2" Sealing Tape	.98 (25)	8.5 (2.6)	.87 (22)	2.0 (50.8)

*Note: The tape will expand in thickness once installed. Measure the gap between or under cabinets/surfaces and select tape to match the thickness range (Min. to Max. thickness).*



**CHATSWORTH PRODUCTS, INC.**

©2012 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame, TeraFrame, GlobalFrame, Cube-iT Plus, Evolution, OnTrac, QuadraRack and Velocity are federally registered trademarks of Chatsworth Products, Inc. eConnect and Simply Efficient are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies. 06/12 MKT-60020-549