



PERFORMANCE SPECIFICATION

TESTING	MINIMUM	TEST METHODS
PEEL STRENGTH	0.30 POUNDS PER INCH WIDTH	40011
MECHANICAL STRENGTH	18 LB PER 0.75 SQUIRE INCHES	UL1565
FLAMMABILITY-20MM	AFTER FLAME TIME INDIVIDUAL ≤30s	UL94-V2 RATING
VERTICAL BURN	TOTAL AFTER FLAME TIME ANY CONDITION ≤250s	
	AFTER FLAME PLUS AFTERGLOW INDIVIDUAL AFTER SECOND FLAME ≤60s	

<p>*** NOTICE ***</p> <p>THIS DOCUMENT CONTAINS CONFIDENTIAL AND/OR PROPRIETARY INFORMATION INTENDED FOR USE ONLY BY THE INDIVIDUAL(S) SPECIFIED HEREIN AND ONLY FOR THE PURPOSE(S) PROVIDED. NEITHER THIS DOCUMENT, NOR ANY INFORMATION CONTAINED HEREIN, MAY BE COPIED, DISTRIBUTED, DISCLOSED TO ANY THIRD PARTY OR USED IN ANY MANNER OTHER THAN FOR WHICH IT HAS BEEN PROVIDED, WITHOUT THE PRIOR WRITTEN CONSENT OF ORTRONICS, INC.</p>	<p>NEW LONDON, CT 06320 (860) 445-3800</p>		<p>TITLE PLEN-TIE, PLENUM HOOK-LOOP STRAPS 1/2" x 8", CRANBERRY, ROLL OF 20</p>			
	DWN.BY: S. LEVESQUE	DATE 02/05/04	SIZE A	CAD FILE 70700143C	PART NUMBER OR-70700143	REV 01
	CHK.BY:		SCALE NONE	DATE 03/23/04	SHEET 1 OF 1	
	APP.BY:					