

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

HBL7545C -- Twist-Lock Plug



2P2W, 15A 125V, L1-15P, Black & White Nylon

Product Specifications

Product Type	 Twist-Lock Devices
Product Item	Plug
Wiring Scheme	2-Pole, 2-Wire Non-Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	L1-15P
Item Style	Standard
Device Color	Black/White
Horsepower	0.5
Cord Dia.	.230"-.720" (5.8-18.3)
Blade Holder Material	Natural White Nylon
Terminal Retainer Material	Clear polycarbonate
Housing Material	Black nylon
Cord Clamp Material	Natural (white) nylon
Blade Material	Brass
Terminal Clamp Material	Cold rolled steel-nickel-plated
Terminal Screw Material	#8-32 Brass (white finish on neutral screw when used)
Cord Clamp Screw Material	Steel-zinc-plated
Body Holding Screw Material	Steel-zinc-plated
Ratings	Molded In or Stamped On

Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	15A #14 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20
Listings	UL
UPC Number	783585178509
Weight in LBs	0.15
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

