



# **KX-UDT Series** SIP Multi-Cell DECT Telephones







KX-UDT121

KX-UDT131



KX-UDS124

SOLUTIONS FOR BUSINESS



# **Big-Building Mobility. SIP Savings & Flexiblity.**

To stay ahead of the curve, large corporations, institutions and small to medium-sized businesses must deftly leverage technologies that cut costs while streamlining operations. The rapid evolution towards SIP-based communications is a vivid example. The ability to transmit voice and data over a single unified network simplifies an institution's IT infrastructure, lowering facility costs along with monthly phone bills. SIP-based solutions have also empowered small businesses with flexible and cost-effective networking solutions that until recently were reserved only for their big-business counterparts.

Large companies and other institutions very often reside in big buildings or campus-style complexes where executives can roam the entire premises, hurrying from meeting to meeting. Likewise, small and medium-sized businesses are typically heavy phone users but can't be deskbound and therefore require on an in-building mobility solution. DECT wireless handsets can keep them connected to their communications hub, assuring important calls don't go unanswered. But is there a comparable solution for those companies large and small who've completely migrated to SIP?

### Introducing the Panasonic SIP Multi-Cell DECT wireless handsets.

Panasonic is known worldwide as a premier manufacturer of communications solutions, including a broad range of flexible, cost-effective SIP endpoints. The Panasonic SIP Multi-Cell DECT series combines the benefits of DECT— an in-building radio technology that delivers high-quality, encrypted, mobile voice transmission—with the widely-accepted SIP standard, paving the way to secure and affordable in-building mobile communications.



prevents accidental dialing.

# **Versatile Wireless Communications**

## **Ergonomically Designed**

The KX-UDT111 is a standard size wireless phone ideal for the general office and any environment requiring enhanced mobility. The slim and light, pocket-sized KX-UDT121 model is perfect for most verticals including retail, hospitality and healthcare facilities where roaming is frequent. A concave shape prevents accidental dialing and protects keys when the handset is in a pocket and keys are rippled for easy access.

The KX-UDT131 is the perfect phone for harsh work environments. With its IP65 compliance (dust and water splash resistant) it is ideal for manufacturing, warehouse or factory applications.



## Large, Colour Display

The KX-UDT Series features a large, 1.8-inch colour thin film transistor (TFT) display with 65,000 colours. The backlit display has easy-to-see icons for optimal viewing.

KX-UDT111

### **High-quality Voice**

Wideband voice technology delivers clear and natural voice. The G.722 wideband audio codec enables high-quality audio by capturing a broader range of audio frequencies, a more complete representation of the audio signal than traditional narrowband.

#### **Hands-free Convenience**

Full-duplex, hands-free convenience and a built-in headset jack make communication even easier. The KX-UDT121 slim and light model even has built-in Bluetooth connectivity for hands-free calling.

#### **Engineered to Perform**

All models support 200 hours of standby time and extensive talk time. The KX-UDT121 and KX-UDT131 provides 13 hours (narrowband) or 10 hours (wideband) talk time, plus a quick charge time of just 3 hours. The KX-UDT111 provides 11 hours (narrowband) or 9 hours (wideband) talk time.

### **Noise Reduction**

Panasonic leads the industry for noise reduction technology that smooths communication in a loud environment. The KX-UDT Series employs technology that estimates and subtracts the noise component from the input signal to deliver best-in-class voice quality.



Incoming signal automatically adjusts according to ambient noise level for maximum clarity.



**KX-UDT111** Standard Model



Slim, Compact Model



KX-UDT131 Rugged Model

# Features that keep business moving

- DECT 6.0 Technology
- 1.8-inch, 65,000-colour TFT Display
- Wideband Voice (G.722)
- Built-in Bluetooth (KX-UDT121)
- Headset Jack (2.5mm plug)
- Vibrate Mode
- 500-Entry Personal Phonebook
- Full-Duplex Speakerphone
- Adjustable Ringtones
- Maximum Register Handsets: 255
- Maximum Cell Stations per System: 128 (32 per Air Sync Group)
- IP65 Compliance (UDT131 only)

## **Smart Connections for Large Facilities**

Big properties can present big communications challenges. Workers can't afford to lose touch with colleagues or customers whenever they walk to another part of the facility. Panasonic SIP Multi-Cell DECT keeps everyone connected because it lets you take the functionality of your desk phone anywhere on the premises. Need to track down the maintenance man? Reach him instantly whether he's in the machine shop or on the roof. Need urgent help with a computer? Connect with IT staff, no matter where they might be on the premises. Never miss an important customer call because you had to walk over the warehouse.

The SIP Multi-Cell DECT series is an ideal solution for workers at large facilities with staff that can't be tied down to a desk. Unlike cumbersome walkie-talkie systems or cell phones, Panasonic SIP Multi-Cell DECT keeps you connected to your company's communications hub with a cost-effective wireless solution that's secure, reliable and interference free.

#### SIP Multi-Cell DECT is the ideal solution for staff in large facilities who need to move about the premises.









Warehouse Staff

#### Healthcare Workers



Maintenance Staff

## Mobility Solutions for SMB

Does your business require you to move around the workplace but keep close to the phone? Panasonic SIP Multi-Cell DECT lets you be mobile while still being connected. Retailers can service customers on the floor without missing customer calls. Online merchants can walk to the warehouse and check inventory while keeping the customer on the line. Panasonic SIP Multi-Cell DECT is ideal for restaurants, fitness clubs, law firms, or any business where you need to field incoming calls but can't sit by the phone.

## **Simple Installation and Maintenance**

The Panasonic SIP Multi-Cell DECT solution is engineered for easy configuration and maintenance. Firmware and settings are wirelessly downloaded to the handsets from a PC or server. There's no need to gather them up individually so you save time on installation and any future updates.

## **Open Source Platform Certification**

Like all phones in the Panasonic SIP lineup, the SIP Multi-Cell DECT series is certified for use with BroadSoft<sup>®</sup> BroadWorks<sup>®</sup>, Digium<sup>®</sup> Asterisk<sup>®</sup> and many others<sup>\*</sup>. They're a proven solution for companies who want to combine a large-complex mobility solution with the cost savings of open-source SIP technology.

\*Consult your Panasonic representative for a complete, up-to-date list.



## **SIP Multi-Cell DECT Series Specifications**

| MODEL NUMBER  |  | KX-UDT111<br>Standard  | <b>KX-UDT121</b><br>Slim, Compact   | KX-UDT131<br>Rugged   |
|---|--|--|---|---|
| SPECIFICATIONS  |  |  |   |   |
| LCD Display Size/Type   |  | 1.8 inch, 65000 colour TFT   | 1.8 inch, 65000 colour TFT  | 1.8 inch, 65000 colour TF   |
| LCD Display Format  |  | 6 lines  | 6 lines   | 6 lines   |
| Brightness Setting  |  | 6 levels   | 6 levels  | 6 levels  |
| Backlight   |  | Y  | Y   | Y   |
| POWER   |  |  | Liter 0.7. 700mAb   | Liter 0.74700mAh  |
| Rechargeable Battery<br>Battery Life  | Talk Time                                    | AAA NiMH, 700mAh, 2 cells<br>Approximately 11 hours  | Li-ion, 3.7v 700mAh<br>Approximately 13 hours   | Li-ion, 3.7v 700mAh<br>Approximately 13 hours   |
| Dattery Life  | Standby                                      | 200h   | 200h  | 200h  |
|   | Charge Time                                  | 7 hours  | 3 hours   | 3 hours   |
| INDICATORS  |  |  |   |   |
| Menu Driven User Int  | erface                                       | Y  | Y   | Y   |
| Line Status   |  | Y  | Y   | Y   |
| Message Waiting Indi  | cator  | LCD Icon   | LCD Icon  | LCD Icon  |
| KEYS  |  |  |   |   |
| Soft Keys   |  | 3  | 3   | 3   |
| Talk / Speaker Phone  | -  | Y  | Y   | Y   |
| 4 Direction 'Nav' Key + Enter   |  | Y  | Y   | Y   |
| Talk / Speaker Phone Key  |  | Y  | Y   | Y   |
| Hold / Message Key  |  | Y  | Y   | Y   |
| VOICE CODECS  |  | 0.700  | 0.700   | 0.700   |
|   |  | G.722<br>G.711 (u-law, a-law)  | G.722   | G.722   |
|   |  | G.711 (u-law, a-law)<br>G.729a   | G.711 (u-law, a-law)<br>G.729a  | G.711 (u-law, a-law)<br>G.729a  |
|   |  | G.729a<br>G.726  | G.729a<br>G.726   | G.729a  |
| HANDS-FREE SPEAKER  | PHONE  | 0.720  | 0.720   | 0.720   |
| HD Speakerphone   |  | Y  | Y   | Y   |
| Volume Control  |  | Y  | Y   | Y   |
| Mute  |  | Y  | Y   | Y   |
| Full Duplex   |  | Y  | Y   | Y   |
| <b>OPERATING CONDITION</b>  | S  |  |   |   |
| Temperature   |  | 0°C - 40°C (32°F - 104°F)  | 0°C - 40°C (32°F - 104°F)   | 0°C - 40°C (32°F - 104°F  |
|   |  |  |   |   |
| RINGTONE CONTROL  |  |  |   |   |
| Vibrate   |  | Y  | Y   | Y   |
| Vibrate<br>Ringtone Selection   |  | Y  | Y   | Y   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level  |  | Y<br>Y   | Y<br>Y  | Y<br>Y  |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C   |  | Y<br>Y<br>Y  | Y<br>Y<br>Y   | Y<br>Y<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S  |  | Y<br>Y   | Y<br>Y  | Y<br>Y  |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES  | IP Signalling                                | Y<br>Y<br>Y<br>Y   | Y<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y  |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration   | IP Signalling                                | Y<br>Y<br>Y<br>Y<br>4  | Y<br>Y<br>Y<br>Y<br>4   | Y<br>Y<br>Y<br>Y<br>4   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book   | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries   | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries  | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries  |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV   | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y  | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y   | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book   | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y<br>Incoming: 20 Entries  | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y<br>Incoming: 20 Entries   | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y<br>Incoming: 20 Entries   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV   | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y  | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y   | Y<br>Y<br>Y<br>Y<br>4<br>500 Entries<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br><b>PHONE FEATURES</b><br>Multiple Registration 1<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial  | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries   | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries  | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries  |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration 1<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)   | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y  | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y   | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI  | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y   | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y  |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLII<br>Anonymous Call Reje  | IP Signalling<br>Support                     | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y   | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>SOO Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y   | Y<br>Y<br>Y<br>Y<br>SOO Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y  |
| Vibrate<br>Ringtone Selection<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>Y<br>Solo Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y   | Y<br>Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLII<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>Y<br>Solo Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y   | Y<br>Y<br>Y<br>Y<br>Y<br>Solo Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>V<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y  |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y   | Y<br>Y<br>Y<br>Y<br>Solo Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration 1<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>A<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>A<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y  | Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y   |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br><b>PHONE FEATURES</b><br>Multiple Registration 1<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y   | Y<br>Y<br>Y<br>Y<br>300 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                               | Y<br>Y<br>Y<br>Y<br>Solo Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>V<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                                       |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br><b>PHONE FEATURES</b><br>Multiple Registration 1<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND,<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold<br>Call Forwarding  | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                                   | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold<br>Call Forwarding<br>Call Waiting   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y           | Y<br>Y<br>Y<br>Y<br>300 Entries<br>300 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                    | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y           |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration :<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold<br>Call Forwarding<br>Call Waiting<br>Voicemail Access  | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y | Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y | Y<br>Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                    |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI<br>Anonymous Call Rejection (Manua<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold<br>Call Forwarding<br>Call Waiting<br>Voicemail Access<br>Flash Hook   | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y      | Y<br>Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y      | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                         |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration :<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLII<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Call Hold<br>Call Forwarding<br>Call Vaiting<br>Voicemail Access<br>Flash Hook<br>Auto Answer  | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                              | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y           | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                         |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manue<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold<br>Call Forwarding<br>Call Vaiting<br>Voicemail Access<br>Flash Hook<br>Auto Answer<br>One-Touch Dial  | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>A<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                    | Y<br>Y<br>Y<br>Y<br>A<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                         | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                         |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration 1<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manue<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Call Hold<br>Call Forwarding<br>Call Hold<br>Call Forwarding<br>Call Waiting<br>Voicemail Access<br>Flash Hook<br>Auto Answer<br>One-Touch Dial<br>Key Lock  | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                              | Y<br>Y<br>Y<br>Y<br>300 Entries<br>4<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y               | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                         |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration 1<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI)<br>Anonymous Call (CLI)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold<br>Call Forwarding<br>Call Forwarding<br>Call Forwarding<br>Call Forwarding<br>Call Forwarding<br>Call Hook<br>Auto Answer<br>One-Touch Dial<br>Key Lock<br>Automatic Key Lock  | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                              | Y<br>Y<br>Y<br>Y<br>300 Entries<br>4<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y               | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>V<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                         |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manua<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Call Hold<br>Call Forwarding<br>Call Forwarding<br>Call Forwarding<br>Call Hold<br>Call Forwarding<br>Call Hold<br>Call Forwarding<br>Call Hold<br>Call Forwarding<br>Call Waiting<br>Voicemail Access<br>Flash Hook<br>Auto Answer<br>One-Touch Dial<br>Key Lock<br>Range Alarm | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y      | Y<br>Y<br>Y<br>Y<br>S00 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y           | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y |
| Vibrate<br>Ringtone Selection<br>Ring Volume Level<br>Ringtone Based on C<br>Ringtone Based on S<br>PHONE FEATURES<br>Multiple Registration S<br>Phone Book<br>Import/Export to TSV<br>Call Log<br>Redial<br>Do Not Disturb (DND)<br>Anonymous Call (CLI)<br>Anonymous Call Reje<br>Calling Party ID<br>Call Rejection (Manue<br>DTMF Dialing During<br>3-Way Conference<br>Attended Transfer<br>Blind Transfer<br>Call Hold<br>Call Forwarding<br>Call Vaiting<br>Voicemail Access<br>Flash Hook<br>Auto Answer<br>One-Touch Dial  | IP Signalling<br>Support<br>)<br>R)<br>ction | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                              | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>Outgoing: 20 Entries<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y           | Y<br>Y<br>Y<br>Y<br>500 Entries<br>Y<br>Incoming: 20 Entries<br>Outgoing: 20 Entries<br>V<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y<br>Y                         |

## **DECT Cell Station Specifications**

| MODEL NUMBER   | <b>KX-UDS124</b><br>4-channel wideband Cell Station<br>with Multi-cell capability |  |  |  |  |
|--|---|--|--|--|--|
| Max Simultaneous calls                                   | 4 calls   |  |  |  |  |
| Max handsets   | Up to 255   |  |  |  |  |
| Max no. of Cell Stations                                 | 128 total; 32 per air sync group  |  |  |  |  |
| Network Interfaces                                       | 10baseT/100baseTX auto<br>MDI/MDI-X Ethernet LAN port                             |  |  |  |  |
| Power Source   | Power over Ethernet (IEEE802.3af) class 1   |  |  |  |  |
| AC Adapter   | (KX-A239) optional  |  |  |  |  |
| Operating Conditions                                     | 0°C - 40°C (32°F - 104°F)   |  |  |  |  |
| CONFIGURATION  |   |  |  |  |  |
| Embedded Web Server                                      | Y   |  |  |  |  |
| Password protected admin access                          | Y   |  |  |  |  |
| BUSINESS FEATURES (REQUIRES SIP SER                      | VER SUPPORT)  |  |  |  |  |
| Network based conference                                 | Y   |  |  |  |  |
| Call Forward / DND sync                                  | Y   |  |  |  |  |
| Connected Line ID presentation                           | Y   |  |  |  |  |
| Direct Inward Dialling (DID)                             | Y   |  |  |  |  |
| Direct Dialling in (DDI)                                 | Y   |  |  |  |  |
| NETWORK CONFIGURATION                                    |   |  |  |  |  |
| DHCP / Static IP address                                 | Y   |  |  |  |  |
| DNS (Primary / Secondary)                                | Y   |  |  |  |  |
| SNTP – Simple network time protocol TIME & DATE HANDLING | Y   |  |  |  |  |
| Clock  | Y   |  |  |  |  |
| Call Timer   | Y   |  |  |  |  |
| Daylight savings time support                            | Y   |  |  |  |  |
| QUALITY OF SERVICE                                       | 1   |  |  |  |  |
| DSCP   | Y   |  |  |  |  |
| Static VLAN  | Y   |  |  |  |  |
| ToS  | Y   |  |  |  |  |
| VOICE QUALITY  |   |  |  |  |  |
| Adaptive Jitter Buffer                                   | Y   |  |  |  |  |
| Configurable Packetization Period                        | Y   |  |  |  |  |
| FEATURES   |   |  |  |  |  |
| Codec Support  | G.722 / G.711 (ulaw, alaw) / G.729a / G.726                                       |  |  |  |  |
| Configurable codec preferences                           | Y   |  |  |  |  |
| Adjustable Codec frame size                              | Y   |  |  |  |  |
| CUSTOMIZABLE TONE GENERATION                             |   |  |  |  |  |
| Dial Tone  | Y   |  |  |  |  |
| Ringing Tone   | Y   |  |  |  |  |
| Busy Tone<br>Reorder Tone                                | Y   |  |  |  |  |
| Stutter Tone   | Y Y   |  |  |  |  |
| MANAGEMENT & PROVISIONING                                | · · · · · · · · · · · · · · · · · · ·   |  |  |  |  |
| Web browser configuration                                | Y   |  |  |  |  |
| Status and stats display                                 | Y   |  |  |  |  |
| Remote firmware upgrade                                  | HTTP, HTTPS, TFTP, FTP  |  |  |  |  |
| 'Over the air' software upgrade                          | Y   |  |  |  |  |
| Remote configuration file download                       | HTTP, HTTPS, TFTP, FTP  |  |  |  |  |
| Panasonic Redirect Server                                | Y   |  |  |  |  |
| Auto provisioning with<br>Panasonic's Redirect Server    | Y   |  |  |  |  |
| TR-069 for remote management                             | Future Support  |  |  |  |  |
| Pre-provisioning by DHCP Opt.66                          | Y   |  |  |  |  |
| Dial plan  | Y   |  |  |  |  |
| Online CS monitor  | Y   |  |  |  |  |
| SECURITY   |   |  |  |  |  |
| Encrypted configuration files                            | Y   |  |  |  |  |
| MD5 authentication                                       | Y   |  |  |  |  |
| HTTPS Server authentication                              | Y   |  |  |  |  |
| DECT encryption  | Y   |  |  |  |  |

For more information, visit the business products, Office Products, business phones section of www.panasonic.ca