

TALKBACK CEILING SPEAKER MODEL V-1060A

FEATURES:

UTILIZES STANDARD CAT 3, 5, OR 6 CABLE

USED WITH TALKBACK PAGE CONTROLS

EXCELLENT VOICE AND MUSIC REPRODUCTION

WIDE SOUND DISPERSION

ELECTRICALLY, ACOUSTICALLY MATCHED COMPONENTS

STURDY STEEL GRILLE



DESCRIPTION:

Ceiling Flush mounted 8" speaker assembly, complete with 45 ohm speaker and round grille.

SPECIFICATIONS:

SPEAKER ELEMENT

Cone Diameter: 8" (20.32 cm)
Voice Coil Impedance: 45 Ohms

INPUT

Impedance: 45 Ohms nominal
Rated Power: 12 Watts

SPEAKER FREQUENCY RESPONSE

80 Hz to 12 kHz

ENVIRONMENT

Temperature: -4 ° to +131 °F (-20 to +55 °C)
Humidity: 0-95% Non-Condensing

HOUSING AND FINISH

Steel grille finished in semi-gloss white enamel.

DIMENSIONS AND WEIGHT

Speaker: 8.00" (20.32 cm)
Grille: 13.0" (33.02 cm)
Shipping Weight: 3.75 lbs (1.7 kg)

METAL MOUNTING ACCESSORIES

V-9914M-5 Support Bridge (order in quantities of 5)
V-9915M-5 Backbox (order in quantities of 5)
or
V-9916M Bridge and Backbox Combination

ACCESSORIES

External Volume Control Available

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

MODEL V-1060A TALKBACK CEILING SPEAKER

The ceiling flush mounted 8" talkback speaker, Model V-1060A, shall consist of a 45 ohm speaker and round grille. The speaker assembly, housing and hardware shall be electrically and acoustically matched for a frequency response of 80 Hz to 12 kHz.

The speaker element shall be cone type with 5 oz (141.75 g) ceramic magnet. Diameter of speaker cone shall be 8.0" (20.32 cm). Voice coil diameter shall be .75" (1.91 cm). Voice coil impedance shall be 45 ohms. Speakers utilizing an 8 ohm impedance voice coil will not be acceptable.

The grille shall be constructed of steel, finished in semi-gloss white enamel.

The V-9915M-5 Backbox and V-9914M-5 Support Bridge shall be constructed of steel and finished for rust prevention. The backbox shall be acoustically treated. Both the backbox and support bridge shall be available separately in quantities of five (5) or assembled together singly as the V-9916M. The V-9914M-5 shall be used in conjunction with the V-9915M-5.

The maximum dimensions shall be: Speaker and Grille - 13.0" (33.02 cm) dia x 3.0" (7.62 cm) D. Backbox: 12.30" (31.24 cm) dia x 4.02" (10.21 cm) D. Support Bridge: 14.50" (36.83 cm) H x 23.75" (60.33 cm) W x 4.25" (10.80 cm) D.

Shipping Weight shall be approximately: Speaker and Grille: 3.75 lbs (1.7 kg). Support Bridge (qty 5): 9.0 lbs (4.08 kg). Backbox (qty 5): 10.5 lbs (4.76 kg). Bridge and Backbox Assembly (qty 1): 4.75 lbs (2.15 kg)

Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs
(major repairs will be subject to additional charges for parts and labor).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.