

### PAGE PORT PREAMP/EXPANDER MODEL V-1094A

#### FEATURES:

BRUSHED STAINLESS STEEL PLATE

EMBOSSSED MARKINGS FROM 0 TO 10

WALL MOUNTABLE

COMES WITH SINGLE GANG SURFACE MOUNT BOX



#### DESCRIPTION:

The V-1094A is a solid-state audio preamplifier capable of driving 150 Valcom one-way speaker/amplifier assemblies. The V-1094A features a stainless steel plate with embossed numbers and fits a single gang electrical wall box. The page port preamp/expander will interface 600 ohm type page ports to up to 150 Valcom amplified speakers or expand the number of Valcom amplified speakers on a zone by 150.

#### SPECIFICATIONS:

##### IMPEDANCE:

Input: 600 ohms

Output: 8 ohms

##### POWER REQUIREMENTS:

Voltage: -21 to -26 Vdc

Idle Current: 12 mA

Operating Current: 15 mA

##### FREQUENCY RESPONSE:

80 Hz to 10 kHz +/- 3 dB

##### GAIN:

+ 8 dB maximum (into 8 ohm load)

##### HOUSING AND FINISH:

Brushed stainless steel single gang plate with raised number dial scale; skirted black knob and position indicator.

##### MOUNTING:

The V-1094 can be mounted in wall or on surface using single gang electrical box.

##### DIMENSIONS AND WEIGHT:

4.44" (11.28 cm) H x 2.75" (6.99 cm) W x 2.88" (7.32 cm) D

Weight: 0.9 lb (.41 kg)