

D'versiBIT® System



A new twist to an old problem. These flexible steel drill bits are the right tools for installing wire or cable inside existing walls.

It bends to meet your needs! Fishing wire or cable through existing walls used to be frustrating and time-consuming, but the D'versiBIT® has made it as simple as bowing the spring steel shaft in the direction you want to drill and turning on the power. Proven in the field to deliver accurate and professional results in many applications. Bits range from 3/16" to 1" (4.8 to 25.4 mm) in diameter and in shaft length from 12" to 72" (304.8 to 1828.8 mm).

The D'versiBIT® System makes it possible to easily accomplish even complex installations. This patented system attaches a quality drill bit to a long flexible spring steel shaft. When used with the Placement Tool, this flexibility makes it possible to easily manipulate the bit within walls. After drilling, attach a D'versiGRIP to the hole in the drill and pull wire or cable back through the wall.



D'versiBIT® Shipping Tubes

Cat./UPC No.	Description
99104	54" x 1" Shipping Tube B with End. (Sold only in minimum quantity of 6 in same length.)
99105	72" x 1" Shipping Tube B with End. (Sold only in minimum quantity of 6 in same length.)



Type M, Masonry



- For drilling in masonry walls and through plaster.
- Recommended for use with Abrasion Shield to reduce friction and abrasion as the shaft turns against masonry.

Type HS High Speed Steel



- Designed for aggressive cutting in all types of wood.
- High speed bit head ensures longer life.

Bit Diameter In. (mm) Color Code	Shaft Length		Shaft Dia.		Type M Masonry		Type HS High Speed Steel	
	In.	mm	In.	mm	Cat. No.	UPC No.	Cat. No.	UPC No.
1/4" (6.4 mm) Blue	12	304.8	3/16	4.8	—	—	1412D	39913
	18	457.2	3/16	4.8	—	—	1418D	38744
	24	609.6	3/16	4.8	—	—	1424D	38745
	36	914.4	3/16	4.8	—	—	1436D	38746
3/8" (9.5 mm) Black	12	304.8	3/16	4.8	—	—	3812D	39914
	18	457.2	3/16	4.8	06-03-18M	38665	3818D	38749
	24	609.6	3/16	4.8	—	—	3824D	38750
	36	914.4	3/16	4.8	—	—	3836D	38751
	54	1371.6	3/16	4.8	06-03-54M	38668	3858D	38752
1/2" (12.7 mm) Green	72	1828.8	3/16	4.8	—	—	3872D	38753
	36	914.4	3/16	4.8	—	—	1236D	38756
	54	1371.6	3/16	4.8	—	—	1258D	38757
	72	1828.8	3/16	4.8	—	—	1272D	38758
	54	1371.6	1/4	6.4	08-04-54M	38678		

D'versiBIT® System

D'versiBIT® Shipping Tubes

Cat./ UPC No.	Description
99104	54" x 1" Shipping Tube B with End. (Sold only in minimum quantity of 6 in same length.)
99105	72" x 1" Shipping Tube B with End. (Sold only in minimum quantity of 6 in same length.)

Type A, Auger



- Wood-type auger bit with screw point.
- Pulls itself through wood, avoids walking or skidding.
- Excellent for drilling in soft woods or through thin sections.
- Slow back-taper allows for easy retrieval.

Type B, Combination with Screw Point



- For aggressive chip removal in many types of woods.
- Screw point for easy starting and pulling through wood.
- With screw point removed, this bit can be ground to function like a standard combination bit.

Type C, Combination



- For drilling in tough woods and thick obstacles.
- Drilling speed relative to pressure applied.
- Chips can be brought easily out of the hole.

Bit Dia. In. (mm)	Shaft Length		Shaft Dia.		Type A Auger		Type B Combination with Screw Point		Type C Combination	
	In.	mm	In.	mm	Cat. No.	UPC No.	Cat. No.	UPC No.	Cat. No.	UPC No.
1/4" (6.4 mm)	36	914.4	5/32	4.0	—	—	—	—	04-03-36C	38112
	54	1371.6	5/32	4.0	—	—	—	—	04-03-54C	38113
	72	1828.8	5/32	4.0	—	—	—	—	04-03-72C	38114
3/8" (9.5 mm)	36	914.4	3/16	4.8	06-03-36A	38067	06-03-36B	38092	06-03-36C	38117
	54	1371.6	3/16	4.8	06-03-54A	38068	06-03-54B	38093	06-03-54C	38118
	72	1828.8	3/16	4.8	06-03-72A	38069	06-03-72B	38094	06-03-72C	38119
1/2" (12.7 mm)	36	914.4	3/16	4.8	08-03-36A	38072	08-03-36B	38097	08-03-36C	38122
	54	1371.6	3/16	4.8	08-03-54A	38073	08-03-54B	38098	08-03-54C	38123
	72	1828.8	3/16	4.8	08-03-72A	38074	08-03-72B	38099	08-03-72C	38124
9/16" (14.3 mm)	36	914.4	3/16	4.8	09-03-36A	38077	09-03-36B	38102	—	—
	54	1371.6	3/16	4.8	09-03-54A	38078	09-03-54B	38103	09-03-54C	38128
	72	1828.8	3/16	4.8	09-03-72A	38079	09-03-72B	38104	09-03-72C	38129
3/4" (19.1 mm)	36	914.4	1/4	6.4	12-04-36A	38082	—	—	—	—
	54	1371.6	1/4	6.4	12-04-54A	38083	—	—	12-04-54C	38133
	72	1828.8	1/4	6.4	12-04-72A	38084	—	—	12-04-72C	38134
1" (25.4 mm)	36	914.4	1/4	6.4	16-04-36A	38087	—	—	—	—
	54	1371.6	1/4	6.4	16-04-54A	38088	—	—	—	—
	72	1828.8	1/4	6.4	16-04-72A	38089	—	—	—	—

Placement Tool



- Allows placement of the drill bit at any point within the wall.
- Helpful in judging where the bit will be during drilling to avoid accidentally drilling through the wall.
- Useful for vertical and horizontal placements.

Cat. No.	UPC No.	Description
712P	38350	D'versiBIT® Placement Tool

SPECIFICATIONS

Function: Use to position all bit and shaft sizes.



Wire and Cable Pulling Grips



- Clip attaches to hole in bit, mesh basket holds wire or cable during recovery, swivel reduces twisting.
- For use with bit 3/8" (9.5 mm) diameter or larger.
- A variety of sizes for pulling wire and cable.

Cat. No.	UPC No.	Description
125	38691	D'versiGRIP for pulling single wire with 3/8" to 1/2" (9.5 mm to 12.7 mm) bits.
150	38692	D'versiGRIP for pulling 1/2" (12.7 mm) OD wire with 1/2" to 9/16" (12.7 to 14.3 mm) bits.
168	38693	D'versiGRIP for pulling 3/4" (19.1 mm) OD wire with 3/4" to 1" (19.2 to 25.4 mm) bits.

SPECIFICATIONS

Function: For pulling wire, cable or fish tape through walls.

Abrasion Shield



SPECIFICATIONS

Function: Protects shaft and hand while drilling with any size or type D'versiBIT®.
 Length: 48" (1219.2 mm)

- Tube fits both shaft sizes.
- Prevents insulation from wrapping around bit shaft.
- Protects shaft of masonry bits as they turn against masonry walls.
- Protects hand holding shaft during drilling.

Cat. No.	UPC No.	Description
606AS	38696	Abrasion Shield

Extensions



SPECIFICATIONS

Size:
 3XT 36, 3XT 54, 3XT 72 - connecting end diameter 7/16" (11.1 mm)
 4XT 36, 4XT 54, 4XT 72 - connecting end diameter 5/8" (15.9 mm)

- Sizes for 3/16" (4.8 mm) and 1/4" (6.4 mm) diameter shafts.
- Connect to chuck end of D'versiBIT® shaft to increase the length of the bit.

Cat. No.	UPC No.	Use With	
		Shaft Dia.	Length
3XT 36	38685	3/16" (4.8 mm)	36" (914.4 mm)
3XT 54	38686	3/16" (4.8 mm)	54" (1371.6 mm)
3XT 72	38687	3/16" (4.8 mm)	72" (1828.8 mm)
4XT 36	38688	1/4" (6.4 mm)	36" (914.4 mm)
4XT 54	38689	1/4" (6.4 mm)	54" (1371.6 mm)
4XT 72	38690	1/4" (6.4 mm)	72" (1828.8 mm)