



**Can Assist In
Complying with
ADA Requirements
Associated With The
Hearing Impaired**

Message Centers & Accessories

1 Line Displays V-5332100

Dimensions: 2.25" (5/82m) H x 19.0 (48.26 cm) W x
4.75" (12.07 cm) D
Weight: 3.5 lbs (1.58 kg)

RS/232 to RS/485 Connector Kit V-5332900

An RS485 Repeater Is Required When More Than 29
Signs Are Used In A Network Or When The Total
Cabling Distance Exceeds 6,000 Feet.

Wireless Keyboard V-5332905

For programming messages and display of message
center sign (V-5332100).

Operates from 4 Triple A Batteries. Will communicate
with Visual Message Center from 20 to 30 feet away.
Once a Visual Message Center is Programmed with
the messages to be displayed other Message Centers
in the same network can be down loaded with the
same messages.

**When Used With The PagePac Plus,
Provides Simultaneous Audio &
Visual Paging. Ideal for high noise
areas, retail advertising or emergency
messages.**

- Compatible with RS/232 port of PagePac Plus Controller
- Capability of one-line display of 2.1" high characters
- Messages are stored in sign and retained even in power interruptions
- Display of messages are in 25 attention-getting modes, 8 true colors and 3 rainbow effects
- Included are various graphic displays and the time of day