

# QuickPort® Field-Configurable Connector Housings

**NEMA-Style Housings** 

### **APPLICATION**

Field-configurable housings in several NEMA styles that accept all individual QuickPort® snap-in modules (sold separately). Use to support multimedia applications where a flush-mount electricalwallplate look is desired, or where there will be multiple devices or a combination of electrical and voice/data devices—under a multi-gang wallplate.

## STANDARDS COMPLIANCE

Meets or exceeds all applicable standards: UL Listed; CSA Certified; Complies with NEC® Article 800 and TIA/EIA-568-B; and meets FCC Part 68.

## PHYSICAL SPECIFICATIONS

Materials: High-impact, fire-retardant plastic rated UL

94V-0

Capacity: Quad 106: 1-4 ports. Duplex 106: 1-2 ports Dimensions: Quad 106: 1.3"W x 4.1"H x 1.178" D (loaded)

Duplex 106: 1.5"W x 4.1"H x 1.2" D (loaded) TR Plus 106: 1.5"W x 4.1"H x 1.2" D (loaded)


#### **DESIGN CONSIDERATIONS**

- Use where an electrical-outlet look & flush-mounting are
- Fits most locations where NEMA duplex opening exists (including floor monuments, access floor boxes, power poles, poke-through fixtures, etc.).
- Gangable in single or multiple gangs.
- If ganged with electrical devices, a barrier box must be used.
- Put blanks (PN# 41084-B\*B) in unused ports for future expansion.
- Specify port identification method (colored modules, designation labels, and custom silkscreening are available). To ID ports, use different colored jacks for each application (full selection of TIA/ EIA-606 compatible colors—13 available), or Leviton's pre-printed Port Designation Labels. (PN#:41080 LXB)

## **UNIQUE FEATURES**

- Four color choices (Ivory, White, Grey, Black).
- Fits within minimum NEMA openings.
- Compatible with all individual QuickPort modules.
- Brass threaded insert for wallplate screw facilitates installation.
- Narrow module width allows high port density in a small area.
- The Quad 106 features a built-in termination station.







# **INSTALLATION NOTES**

- Terminate jacks/modules, then snap them into housing from the rear; housing screws to box, and NEMA plate screws to
- Detailed installation instructions are included in the carton.
- Break off "T" arms for floor monument installation.
- The Quad 106 "Termination Station" (built-in termination aid) stabilizes jacks during punchdown.

For ELECTRONIC Typical Specs see (.TXT) file on disk.

### TYPICAL SPECIFICATION

The workstation jack/connector housing shall be a fieldconfigurable NEMA-style housing that mounts flush in standard NEMA openings, and under standard duplex electrical wallplates in single or multiple gangs. It should provide ports which are fieldconfigurable with a variety of simplex snap-in jacks/modules. Must be constructed of high-impact, fire-retardant plastic rated UL 94V-0, and be UL Listed, CSA Certified, and compliant with FCC Part 68 and TIA/EIA-568-B specifications. Colors, configurations and related wallplates to be specified per schedule on plan. The manufacturer shall provide a one-year limited product warranty and 15 year product performance guarantee. The manufacturer shall provide a lifetime warranty against defects in material and workmanship and an application guarantee when installed as part of a certified system.

# WARRANTY INFORMATION

- Two-year limited product warranty
- Product and performance warranties are extended to a Lifetime as part of Leviton's Certified Cabling System.



For Applications Engineering Support - Call 1-425-485-4288; in USA call 1-800-722-2082 Spec sheets and updates are also available at www.levitonvoicedata.com.




# QuickPort® Field-Configurable Connector Housings

Part Numbers 41087-xxP


#### **DIMENSIONAL LINE ART**

See ELECTRONIC FILES for CAD images (.DXF, .DWG, MS-DOS.EPS)

QuickPort® Quad 106 Flush Mount Jack



QuickPort® Duplex Flush Mount Jack



#### PART NUMBER

QuickPort® Field-Configurable Connector Housings	Part No.
Quad 106	41087-Q*P
Duplex 106	41087-2*P

<sup>\* =</sup> color Ivory (I), White (W), Grey (G), Black (E).

Note: QuickPort® snap-in modules (jacks and bulkhead connectors and couplings), Decora® wallplates and Decora Plus® wallplates are sold separately. Please refer to the QuickPort ® module spec sheets and the Leviton catalog for ordering information.





For Applications Engineering Support – Call 1-425-485-4288; in USA call 1-800-722-2082. Spec sheets and updates are also available at www.levitonvoicedata.com.



2222 - 222nd St. SE • Bothell, WA 98021 USA • Tel: 1-800-722-2082 / 1-425-485-4288 • Fax: 1-425-483-5270 • Int'l Fax: 1-425-485-9170 • GSA# GS-35F-4785G