
























# Decorra Wallplates

## Standard Size Smooth Plastic Wallplates

DESCRIPTION	CAT. NO.	COLOR*
<b>1-GANG</b> 	80401	I, W, GY, E, A
<b>2-GANG</b> 	80409	I, W, GY, E, A
<b>2-GANG 1-Decora 1-Toggle</b> 	80405	I, W, GY, E, A
<b>2-GANG 1-Decora 1-Duplex</b> 	80455	I, W, A
<b>2-GANG 1-Decora 1-Telephone (.406 in hole)</b> 	80479	I, W
<b>3-GANG</b> 	80411	I, W, GY, E, A
<b>3-GANG 2-Decora 1-Toggle</b> 	80431	I, W, GY
<b>3-GANG 2-Toggles 1-Decora</b> 	80421	I, W, GY, E, A
<b>3-GANG 1-Decora 1-Toggle 1-Telephone</b> 	80442-1	Ivory Only
<b>3-GANG 2-Decora 1-Telephone</b> 	80443-1	Ivory Only
<b>4-GANG</b> 	80412	I, W, GY, A, E
<b>5-GANG</b> 	80423	I, W, GY, A, E
<b>6-GANG</b> 	80436	I, W, GY, A, E
<b>7-GANG</b> 	80407	I†, W†
<b>8-GANG</b> 	80408	I†, W†

†Painted metal wallplate.

## Midway Size Smooth Plastic Wallplates

DESCRIPTION	CAT. NO.	COLOR*
<b>1-GANG</b> 	80601	I, W, GY, A
<b>2-GANG</b> 	80609	I, W, GY, A
<b>2-GANG 1-Blank 1-Decora</b> 	80608	I, W, A
<b>2-GANG 1-Decora 1-Toggle</b> 	80605	I, W, A
<b>3-GANG</b> 	80611	I, W, A
<b>4-GANG</b> 	80612	I, W, A

All devices are UL Listed and CSA Certified.



80405-W



Decorra Standard/Midway wallplate size comparison (3/8" wider and longer), 80401 in front of 80601.

### SPECIFICATIONS & FEATURES

- A wide selection of sizes and colors to blend with any wall covering
- Smooth face and rounded edges that resist dust accumulation
- Individual plastic wrapping to protect surfaces
- Color-matched mounting screws supplied

### TESTING & CODE COMPLIANCE

- UL Listed (File #E-13397)
- CSA Certified (File #LR-16347)
- NOM Certified (#057)
- Full compliance with NEMA Standards WD-1
- Backed by a Limited Two-Year Warranty

### \*COLOR

Basic Cat. No. denotes Mahogany device. For other color selections, add suffix to the catalog number as follows: Ivory (-I), White (-W), Gray (-GY), Black (-E) and Almond (-A).

### MATERIAL CHARACTERISTICS

Environmental: Flammability UL-94, V2 Rating  
Operating Temperature: -40°C to 120°C



For more information regarding matching wallplates, colors, materials, single and multi-gang, refer to Wallplates, section G.