



Not intended for rack-mount servers

## QuadraRack® 4-Post Frame

The QuadraRack® 4-Post Frame offers the strength and stability of a cabinet in an open mounting system. Enjoy easy equipment installation along with unrestricted airflow for improved cooling and heat dissipation.

- 19" EIA width
- Manufactured from aluminum
- EIA-310-D Standard Universal 5/8"-5/8"-1/2" (15.9 mm-15.9 mm-12.7 mm) alternating hole pattern, mounting holes are roll-formed #12-24
- Ships unassembled
- Load Rating: 2000 lb (907.2 kg) — weight must be evenly distributed and the rack must be properly secured to the floor

### QuadraRack 4-Post Frame Kit includes:

- (4) Rack Channels
- (2) Base Angles
- (2) Top Angles
- (1) Extension Pan Set
- (1) Bag of 100 Rack mounting screws — Pilot Point #12-24 with combination Phillips/Straight head

Part Number	Description H x W x D Height - ft (m), Depth - in (mm)	Shipping Weight lb (kg)
50120-X03	7 (2.1) x 19 x 29 (740), 45U	65 (29.5)
50120-X15	8 (2.4) x 19 x 29 (740), 51U	67 (30.4)
50120-X08	9 (2.7) x 19 x 29 (740), 58U	69 (31.3)

X=color: 1=Gray, 2=White, 5=Clear, 7=Black

## ExpandaRack

Convert a CPI two-post rack to a QuadraRack with ExpandaRack.



Part Number	Description H x W x D Height - ft (m), Depth - in (mm)	Shipping Weight lb (kg)
<b>ExpandaRack - Standard Rack</b>		
50110-X03	7 (2.1) x 19 x 29 (740), 45U	46 (20.9)
50110-X15	8 (2.4) x 19 x 29 (740), 51U	48 (21.8)
50110-X08	9 (2.7) x 19 x 29 (740), 58U	50 (22.7)
<b>ExpandaRack - Universal Rack</b>		
50130-X03	7 (2.1) x 19 x 29 (740), 45U	52 (23.6)
50130-X15	8 (2.4) x 19 x 29 (740), 51U	55 (24.9)
50130-X08	9 (2.7) x 19 x 29 (740), 58U	58 (26.3)
<b>ExpandaRack - Pan Set (W x D)</b>		
50150-X99	19 x 29 (740) — Std Rack	18 (8.2)
50160-X99	19 x 29 (740) — Universal Rack	18 (8.2)