



DATA PRODUCTS



COMPUTER CABLES

Allen Tel's selection of molded and completely shielded computer cables, when used to tie together the various components of a system or network, assures the user of error-free and trouble-free long term service. Each cable is effectively shielded against both electromagnetic and

radio frequency interference by means of braided copper and aluminum foil. The connectors and outer cable sheath are molded and bonded together to form an integral assembly providing added strain relief and protection from abrasion. Easy-grip extended thumb screws on the con-

nectors speed up installation. Conductors are 26-gauge. Two types are available: cables designed for interconnection between two specific elements of a computer system and cables for more general application which are wired on a pin-to-pin basis.



MONITOR CABLES

Cables terminated at each end in DB9-type connectors either male or female as indicated below; they are normally used between a monitor and computer assembly. The GBDB9MF 5-foot cable and the GBDB9MF 10-foot cable are both terminated in male to female connectors. The 10-foot GBDB9MM is terminated male to male.

- GBDB9MF-5**
- GBDB9MF-10**
- GBDB9MM-10**



PRINTER CABLES

8 or 15-foot cables with DB25 male and CN36 terminations. For use as printer cables for IBM PC, PS/2 or Apple IIE computers.

- GBDB25MCN36M-8 (8 FT.)**
- GBDB25MCN36M-15 (15 FT.)**



PRINTER CABLE

A 6-foot cable with DB9 to DB25 terminations. Used as a printer cable between a MAC computer and a serial printer.

- GBDB25MDB9M-6**



GENERAL USE CABLES

GBDB25MF-3

- DB25M to DB25F. 3 Ft.

GBDB25MF-5

- DB25M to DB25F. 5 Ft.

GBDB25MF-10

- DB25M to DB25F. 10 Ft.

GBDB25MF-15

- DB25M to DB25F. 15 Ft.

GBDB25MF-25

- DB25M to DB25F. 25 Ft.

GBDB25MF-35

- DB25M to DB25F. 35 Ft.

GBDB25MF-50

- DB25M to DB25F. 50 Ft.

GBDB25MM-3

- DB25M both ends. 3 Ft.

GBDB25MM-5

- DB25M both ends. 5 Ft.

GBDB25MM-10

- DB25M both ends. 10 Ft.

GBDB25MM-15

- DB25M both ends. 15 Ft.

GBDB25MM-25

- DB25M both ends. 25 Ft.

GBDB25MM-35

- DB25M both ends. 35 Ft.

GBDB25MM-50

- DB25M both ends. 50 Ft.

