





Power Devices

50 AMP 125V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	WALLPLATE INFORMATION
Flush Mount Receptacle	5373† 5-50R 	Fits all wallplates with 2.15" diameter center hole. See Section G for more information.
Matching Angle Plug	9550-P 5-50P 	





50 AMP 250V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	WALLPLATE INFORMATION
Flush Mount Receptacle	5374† 6-50R 	Fits all wallplates with 2.15" diameter center hole. See Section G for more information.
Flush Mount Receptacle Isolated Ground	5374-IG	As above
Surface Mount Receptacle	5378	
Matching Angle Plug	9650-P 6-50P 	



50 AMP 277V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	WALLPLATE INFORMATION
Flush Mount Receptacle	9750-A† 7-50R 	Fits all wallplates with 2.15" diameter center hole. See Section G for more information.
Matching Angle Plug	9750-P 7-50P 	

†Matching single-gang wallplate: Cat. No. 84028. Matching Industrial Weather-Resistant cover: Cat. No. WP2. All devices are UL Listed and CSA Certified.

SPECIFICATIONS & FEATURES

- Made of durable thermoplastic
- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to No. 4 AWG conductors
- Terminal marked for easy identification and fast wiring
- All mounting hardware included
- Flush-mount devices fit single or two-gang outlet boxes
- Surface-mount devices are COMMERCIAL GRADE and have concentric knockouts for 3/4" and 1" conduit and adjustable cord clamp and back and bottom entrance of cable

TESTING & CODE COMPLIANCE

- UL Listed for copper or aluminum conductors (File #E-13399); Angle Plugs (File #E-13393, File #E-3810)
- UL Test 498
- CSA Certified for copper or aluminum conductors (File #152105); CSA Test 42
- NOM Certified (#057)
- Meets NEMA and ANSI standards
- Backed by a Limited 10-Year Warranty

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: From -40° C (without impact) to 75° C maximum continuous

