

Sold by:



## 19 Series — Ball Nose — Up to 690 AMP,\* 600V

\*Refer to Ampacity Chart for all cable sizes on page JJ2



19R21-E

### Panel Receptacle—Threaded Stud (Cable Size: 250–750MCM)

	90° STYLE		30° STYLE	
	MALE	FEMALE	MALE	FEMALE
COLOR	CAT. NO.	CAT. NO.	CAT. NO.	CAT. NO.
Black	19R21-E	19R22-E	19R23-E	19R24-E
White	19R21-W	19R22-W	19R23-W	19R24-W
Red	19R21-R	19R22-R	19R23-R	19R24-R
Blue	19R21-B	19R22-B	19R23-B	19R24-B
Green	19R21-G	19R22-G	19R23-G	19R24-G
Yellow	19R21-Y	19R22-Y	19R23-Y	19R24-Y
Orange	19R21-O	19R22-O	19R23-O	19R24-O
Brown	19R21-H	19R22-H	19R23-H	19R24-H



19P21-E

### Female Terminal Connector (Cable Size: 250–750MCM)

	ANGLE STYLE	OFFSET STYLE
COLOR	CAT. NO.	CAT. NO.
Black	19F21-E	19F22-E
White	19F21-W	19F22-W
Red	19F21-R	19F22-R
Blue	19F21-B	19F22-B
Green	19F21-G	19F22-G
Yellow	19F21-Y	19F22-Y
Orange	19F21-O	19F22-O
Brown	19F21-H	19F22-H

### Protective Caps

	MALE	FEMALE
COLOR	CAT. NO.	CAT. NO.
Black	19P21-E	19P22-E
White	19P21-W	19P22-W
Red	19P21-R	19P22-R
Blue	19P21-B	19P22-B
Green	19P21-G	19P22-G
Yellow	19P21-Y	19P22-Y
Orange	19P21-O	19P22-O
Brown	19P21-H	19P22-H

### SPECIFICATIONS & FEATURES

- The 19 Series Ball Nose connectors are designed for general industrial applications

