

PJ Junior Duty Series Grips are indispensable tools for electricians with small job requirements. They are used to connect insulated wire bundles to pulling tape or to pull wire rope through conduit.


Pulling Grips—PJ Series S

Single Weave, Flexible Eye, Junior Duty

| CAT. NO. | CABLE DIA. RANGE (INCHES) | APPROXIMATE BREAK STRENGTH* | MESH LENGTH (INCHES) |
|--------------|---------------------------|-----------------------------|----------------------|
| L8500 | 0.25–0.36 | 1,700 | 5 |
| L8501 | 0.37–0.49 | 1,700 | 7 |
| L8502 | 0.50–0.61 | 1,700 | 8 |
| L8503 | 0.62–0.74 | 2,800 | 10 |
| L8504 | 0.75–0.99 | 4,100 | 10 |
| L8505 | 1.00–1.24 | 4,100 | 12 |

Single Weave, Flexible Eye, Junior Duty—Kit

| KIT CAT. NO. | KIT INCLUDES ONE EACH OF CAT. NO. |
|--------------|-----------------------------------|
| L8510 | L8500 |
| | L8501 |
| | L8502 |
| | L8503 |
| | L8504 |
| | L8505 |



PL Light Duty Grips are the most economical pulling grips for many applications, such as industrial plant wiring, rewiring, and underground electrical pulls.

Pulling Grips—PL Series S

Single Weave, Flexible Rope Eye, Light Duty, Short

| CAT. NO. | CABLE DIA. RANGE (INCHES) | APPROXIMATE BREAK STRENGTH* | MESH LENGTH (INCHES) |
|--------------|---------------------------|-----------------------------|----------------------|
| L8511 | 0.50–0.61 | 3,400 | 12 |
| L8512 | 0.62–0.74 | 4,100 | 14 |
| L8513 | 0.75–0.99 | 4,100 | 14 |
| L8514 | 1.00–1.24 | 5,800 | 16.5 |
| L8515 | 1.25–1.49 | 5,800 | 17 |
| L8516 | 1.50–1.74 | 7,500 | 20 |
| L8517 | 1.75–1.99 | 10,000 | 23 |
| L8518 | 2.00–2.49 | 10,000 | 23 |
| L8519 | 2.50–2.99 | 13,000 | 23 |

Single Weave, Flexible Rope Eye, Light Duty, Medium

| CAT. NO. | CABLE DIA. RANGE (INCHES) | APPROXIMATE BREAK STRENGTH* | MESH LENGTH (INCHES) |
|--------------|---------------------------|-----------------------------|----------------------|
| L8523 | 0.50–0.61 | 3,400 | 16 |
| L8524 | 0.62–0.74 | 4,100 | 16 |
| L8525 | 0.75–0.99 | 4,100 | 20 |
| L8526 | 1.00–1.24 | 7,500 | 20 |
| L8527 | 1.25–1.49 | 7,500 | 22 |
| L8528 | 1.50–1.99 | 7,500 | 25 |
| L8529 | 2.00–2.49 | 10,000 | 26 |
| L8530 | 2.50–2.9 | 13,000 | 28 |
| L8531 | 3.00–3.49 | 16,200 | 30 |
| L8532 | 3.50–3.99 | 19,400 | 32 |

Single Weave, Flexible Rope Eye, Light Duty, Medium—Kit

| KIT CAT. NO. | KIT INCLUDES ONE EACH OF CAT. NO. |
|--------------|-----------------------------------|
| L8540 | L8525 |
| | L8526 |
| | L8528 |
| | L8529 |

*To determine workload safety factor, divide approximate break strength by 5. See page Q5 for strength information.

