

ANSI/TIA/EIA 568 Category 5e

Part Number: Plenum5ES4/Non-Plenum5ENS4


Screened 4 Twisted Pair Cable (ScTP)

Plenum: UL Type CMP, C(UL) CMP

Non-Plenum: ETL Type CMR, C(ETL)CMG

Twisted Pair Shielded Cable

- Outer Jacket
PVC
- Pair Insulation
Non-Plenum: PE
Plenum: FEP
- Polyester Tape
- 24 AWG Solid Copper
- Aluminum Tape
- Drain Wire
24 AWG Solid Tinned Copper



Pair Identification – Option 1

Pair 1	Blue/White w/Co-Extruded Blue Stripe on White Single
Pair 2	Orange/White w/Co-Extruded Orange Stripe on White Single
Pair 3	Green/White w/Co-Extruded Green Stripe on White Single
Pair 4	Brown/White w/Co-Extruded Brown Stripe on White Single

Mechanical Specification	Plenum	Non-Plenum
Nominal Jacket OD	0.200"	0.245"
Nominal Jacket Thickness	0.015"	0.020"
Jacket Minimum Spot Thickness	0.013"	0.017"
Installation Temperature 0°C to 60°C		
Operation Temperature -20°C to 60°C		

Available Packaging: Box or Reel
 Available Colors: White, Blue, Gray



Drawings not to Scale
 Specifications subject to change
 Revision: 11/17/08



1100 CommScope Place SE
 PO Box 1729
 Hickory, NC 28603-1729
 (800) 982-1708
 (828) 324-2200
 (828) 328-3400
 Fax: (828) 323-4989
 Int'l Fax: (828) 323-4989
 www.commscope.com



ANSI/TIA/EIA 568 Category 5e

Part Number: Plenum5ES4/Non-Plenum5ENS4

Screened 4 Twisted Pair Cable (ScTP)

Plenum: UL Type CMP, C(UL) CMP

Non-Plenum: ETL Type CMR, C(ETL)CMG

Electrical Performance

Frequency MHz	Attenuation (dB/100m) Max	Pair to Pair		Return Loss (dB) Min	ACR (dB) Min	Power Sum		
		NEXT (dB) Min	ELFEXT (dB/100m) Min			NEXT (dB) Min	ELFEXT (dB/100m) Min	ACR (dB) Min
.772	1.8	67	66	NA	65	64	63	62
1.0	2.0	65	64	20.0	63	62	61	60
4.0	4.0	56	52	23.0	52	53	49	49
8.0	5.8	52	46	24.5	45	48	43	43
10.0	6.5	50	44	25.0	44	47	41	41
16.0	8.2	47	40	25.0	39	44	37	36
20.0	9.2	46	38	25.0	37	42	35	34
25.0	10.4	44	36	24.3	34	41	33	31
31.25	11.7	43	34	23.6	31	40	31	28
62.5	17.0	38	28	21.5	21	35	25	18
100.0	22.0	35	24	20.1	13	32	21	10

(All tests include swept frequency measurements)

NEXT, and Power Sum values are derived from functions and truncated to the nearest whole dB

Input Impedance (Zin)	100 ohms ± 15% 1 – 100 MHz
Capacitance	14 pF/ft nominal
DC Resistance/Unbalance	28.6 ohms/100m Max/ 5% Max
Dielectric Breakdown	2500 Volts DC Conductor to Conductor
Nom. Velocity of Propagation	FEP = 71% PE = 68%
Maximum Skew	45nSec @ 100meters



Drawings not to Scale
 Specifications subject to change
 Revision: 11/17/08