

SLIMLINE ONE-WAY SPEAKER MODEL V-1042

FEATURES:

- UTILIZES STANDARD CAT 3, 5, OR 6 CABLE
- REMOVABLE CLOTH COVERED GRILLE
- BUILT IN HANGER
- HIGH DENSITY POLYPROPYLENE ENCLOSURE
- VOICE AND MUSIC REPRODUCTION QUALITY



DESCRIPTION:

Contemporary designed wall speaker for areas that require a stylish appearance. Used for background music and voice paging, the thick walled, high density polypropylene enclosure minimizes vibrations. Utilizing the built-in hanger, this speaker may be conveniently mounted on the wall. The speaker is available in white, gray, brown and black with a color co-ordinated cloth grille.

SPECIFICATIONS:

SPEAKER ELEMENT

Cone Diameter: 5.0" (12.7 cm)
Voice Coil Impedance: 45 ohms

FREQUENCY RESPONSE

95 Hz to 16 kHz

INPUT

Impedance: ≥ 600 Ohms nominal
Signal Level: -10 dBm line level

OUTPUT

Rating: ≥ 93 dB @ 4' (1.22 m)

ENVIRONMENT

Temperature: -4 to +131 °F (-20 to +55 °C)
Humidity: 0-95% Non-Condensing

HOUSING AND FINISH

High density polypropylene in white, gray, brown or black with color co-ordinated cloth grille.

DIMENSIONS AND WEIGHT

7.0" (17.8cm) H x **10.3"** (26.2 cm) W x **3.8"** (9.6 cm) D
Weight: 2.8 lbs (1.27 kg)

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

MODEL V-1042

SLIMLINE ONE-WAY SPEAKER

The Slimline One-Way Wall Speaker, Model V-1042 shall be constructed of a high density polypropylene with a removable color coordinated cloth covered grille. The unit shall include a 45 ohm speaker, amplifier, and volume control.

The amplifier shall have a frequency response of 95 Hz to 16 kHz. The amplifier shall operate on a -24 Vdc nominal, positive ground power supply. Operating current shall be 50 mA at -24 Vdc. Operating temperature shall be -4 to +131 °F (-20 to +55 °C).

The wall speaker shall have an integral hanger molded in the cabinet.

The dimensions shall be 7.0" (17.8 cm) H x 10.3" (26.2 cm) W x 3.8 (9.6 cm) D. The weight shall be 2.8 lbs (1.27 kg).

Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.

