

Detailed Specifications & Technical Data



8267 Coax - 50 Ohm Cable

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---	---

Description:

13 AWG stranded (7x21) .089" bare copper conductor, polyethylene insulation, bare copper braid shield (96% coverage), non-contaminating PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	213/U
AWG	13
Stranding	7x21
Conductor Diameter	.089 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PE - Polyethylene
Insulation Diameter	.285 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	BC - Bare Copper
Outer Shield %Coverage	96 %

OUTER JACKET:

Outer Jacket Material	PVCNC - Polyvinyl Chloride Non-Contaminating
-----------------------	--

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.405 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
UL Temperature Rating	60°C (UL AWM Style 1354)
Bulk Cable Weight	104 lbs/1000 ft.
Max. Recommended Pulling Tension	184 lbs.
Min. Bend Radius (Install)	5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE: