

NEW!



Fan Top Panel Kit

Use to replace the standard top panel and provide additional exhaust airflow through the top of the cabinet. Two fan housings are mounted on the bottom of the panel. Each fan housing has two 4.5" (114 mm) diameter fans capable of 100 CFM (170 CMH) each and an IEC C14 connector. The kit includes a detachable 15'L (5 m) power cord with dual C13 connectors for the fan housings and a molded NEMA 5-15P plug (115 VAC) or C14 (230 VAC) connector.

Part Number Cabinet Width			Description (Cabinet Depth)	Shipping Weight lb (kg)
600 mm	750 mm	800 mm		
115 VAC Fans, NEMA 5-15P Plug				
N/A	N/A	25088-708	800 mm Cabinet	25 (11.3)
25088-701	25088-705	25088-709	1000 mm Cabinet	29 (13.2)
25088-702	25088-706	25088-710	1050 mm Cabinet	31 (14.1)
25088-703	25088-707	25088-711	1200 mm Cabinet	34 (15.4)
230 VAC Fans, IEC C14 Connector				
N/A	N/A	25088-728	800 mm Cabinet	25 (11.3)
25088-721	25088-725	25088-729	1000 mm Cabinet	29 (13.2)
25088-722	25088-726	25088-730	1050 mm Cabinet	31 (14.1)
25088-723	25088-727	25088-731	1200 mm Cabinet	34 (15.4)

Color is Black. Shipping Weights are for 800 mm part numbers.

Snap-In Filler Panel

Block airflow through open rack-mount spaces to help keep hot air at the back of the cabinet. Snap-In Filler Panels can be used in any 19"W CPI Cabinet that has square-punched equipment mounting rails.



Part Number	Description H x W (in)	Shipping Weight lb (kg)
34537-000	1U x 19, Black, 1 Each	1 (0.5)
34538-000	2U x 19, Black, 1 Each	2 (0.9)
34537-001	1U x 19, Black, 6 Each	4 (1.8)
34538-001	2U x 19, Black, 6 Each	4 (1.8)
34537-002	1U x 19, Black, 50 each	22 (10.0)
34538-002	2U x 19, Black, 50 each	35 (15.9)

Additional accessories available, visit www.chatsworth.com for more information.