



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PDUMH15

Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter

Highlights

- 1U rackmount PDU
- Digital current monitoring display
- 12 rear facing outlets, 1 front facing outlet
- 15-ft cord
- 15-amp breaker
- Switchless design



Description

Tripp Lite's PDUMH15 AC power distribution unit offers a digital current monitor and provides 15 amps of 120 volt capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter, or 1U/0U rackmount installation. Uses only 1U of rack space when installed in any 19-inch rack, with the potential for zero U mounting in the cable management area of most rack enclosures. Built-in digital ammeter display offers continuous visual power consumption data for the entire PDU. Attractive rackmount housing with 1 front and 12 rear facing outlets measures only 4.5 inches in depth. Unfiltered electrical pass-through without a power switch makes the PDUMH15 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets, and more. Includes 12 rear facing NEMA 5-15R and one front facing outlet, 15-ft. AC power cord, 15 amp breaker, TVSS grounding lug and rugged all metal rackmount case design.

Applications

- Multi-outlet power distribution unit with digital current monitoring is the ideal means of powering multiple loads in 19 inch rackmount, wall-mount, and under-counter applications such as internetworking, PC systems, telecommunications, audio visual, security, sound reinforcement, and more. Ideal distribution of alternate and sinewave UPS and generator power or commercially derived AC power to connected equipment.

Package Includes

- PDUMH15 Metered rackmount PDU
- Owner's manual with warranty information

Features

- 120V 15A Metered rackmount AC power distribution unit with 15 amp capacity and 13 AC receptacles
- Front panel digital current monitoring display shows power consumption of connected equipment
- Versital all-metal rackmount cabinet with detachable mounting flanges allows wall-mount, under-counter, and 19-inch rackmount mounting in both 1U and zero U formats
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 13 NEMA 5-15R output receptacles accept common NEMA5-15P equipment plugs
- 15 foot AC power cord with NEMA5-15P plug connection
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 15 amp electrical capacity with circuit breaker
- 120 VAC, 50/60 Hz electrical compatibility

Specifications

| | |
|--|---|
| OVERVIEW | |
| Model Type | Metered |
| SYSTEM OVERVIEW | |
| Voltage compatibility | 120V |
| OUTPUT | |
| Frequency compatibility | 50 / 60 Hz |
| Output nominal voltage | 120V |
| Overload protection | 15A |
| Outlet quantity / type | 13 NEMA 5-15R |
| INPUT | |
| Recommended Electrical Service | 120V |
| Maximum input amps | 15A |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | 15 feet |
| LEDS ALARMS & SWITCHES | |
| Front panel LEDs | Digital LED current monitor display |
| PHYSICAL | |
| Shipping weight (lbs) | 5.2 |
| Unit Dimensions (HWD/in) | 1.75 (1U) x 17.5 x 4.5 |
| Shipping Dimensions (HWD/in) | 2.25 x 20.5 x 10 |
| Unit weight (lbs) | 4.5 |
| Material of construction | Sheet Metal |
| Style | Rackmount, Vertical Rackmount, Wallmount/Under-Counter |
| Form factors supported | 1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation |
| SPECIAL FEATURES | |
| Appearance | All black color scheme |
| TVSS grounding | Rear grounding lug |
| CERTIFICATIONS | |
| Certifications | Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant |
| WARRANTY | |
| Product Warranty Period (U.S., Canada & Puerto Rico) | Lifetime |



Related Items

Optional Products

| Product Type | Related Model | Description | Qty. |
|--------------|--------------------------|---|------|
| Power Cables | P002-002 | 2-ft. Power Cord (IEC-320-C14 to NEMA 5-15R) | - |
| Power Cables | P007-002 | 2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P) | - |
| Power Cables | P007-006 | 6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P) | - |
| Power Cables | P007-010 | 10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P) | - |
| Power Cables | P010-012 | 12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13) | - |
| Power Cables | P012-006 | 6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7) | - |
| Power Cables | P022-001 | 1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P) | - |
| Power Cables | P023-001 | 1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P) | - |
| Power Cables | P034-010 | 10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P) | - |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3457.

© 2010 Tripp Lite. All Rights Reserved.

