

IS-SS-HID

Stainless Steel Flush Mount Audio Door Station with HID® Proximity Reader

DESCRIPTION:


The IS-SS-HID is an audio-only door station for the IS system, with a built in HID® ProxPoint® Plus card reader.

The audio door station can be connected via CAT-5e/CAT-6 wire to any of the following IS exchange units: IS-CCU, IS-SCU, or IS-RCU. Maximum distance from the door station to the exchange unit is 980'.

Wiring and power for the card reader are separate from the intercom wiring. The card reader is to be connected to a host controller of any type that is compatible with the HID® ProxPoint® Plus proximity card reader.

FEATURES:

- Audio door station for IS System
- Stainless steel faceplate
- HID® ProxPoint® Plus proximity card reader built in
- Tamper resistant screws



IS-SS-HID

Stainless Steel Flush Mount Audio Door Station with HID® Proximity Reader

FEATURE CALL-OUT DEFINITIONS:

- [1] Microphone
- [2] Speaker
- [3] Call button
- [4] HID® ProxPoint® Plus proximity card reader

SPECIFICATIONS:

- Power Source: 48VDC (supplied from CEU)
- Communication: Open voice hands-free
- Wiring: CAT-5e or CAT-6
- Wiring distance: 980'
- Door release contact: 24V AC/DC, 500mA (N/O, COM, N/C)
- Operating Temp: 14° - 140°F (-10° - 60°C)
- Dimensions: 7" W x 12-³/₈" H x 1-⁷/₈" D

FEATURE CALL-OUTS:

