

## Clarity 6 angled 24-port Category 6 patch panel, high density, six-port modules, 19" x 1.75" - OR-PHA66U24

Clarity<sup>6</sup> angled 24-port Category 6 patch panel, high density, six-port modules, 19" x 1.75".



### FEATURES

- Recessed design with lower mounted profile
- ETL verified to TIA Category 6 component spec
- Center tuned to Clarity<sup>6</sup> patch cords
- Universally wired 110 termination
- New IDC housing
- Supplied rear cable management
- High density design
- RoHS compliant

### BENEFITS

Sold by:



- Directs cords more easily to vertical management
- Ensures component performance
- More transparent mated union
- Supports T568A and T568B installs
- Handles larger Category 6 conductors
- Supports good cabling practice
- Maximizes rack utilization
- Lead free

## Specifications

### DIMENSION INFO

Height Metric: 44.45 mm

Width Metric: 482.6 mm

Cable Diameter Range: 22-26 AWG

Depth Metric: 46.23 mm

Height U S: 1.75"

### GENERAL INFO

Mod Jack Wiring: Universal T568A/B

Number Of Ports: 24

### TECHNICAL INFO

Performance Rating: Category 6

Category Rating: Category 6

### CONSTRUCTION INFO

Component1: Panel - Material1: .090" Aluminum, Finish\_Plating1: Painted black texture with blue silkscreen

Component4: Array of eight modular dual reactance Category 6 contacts - Material4: Beryllium Copper,

Finish\_Plating4: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Component5: IDC contacts (low noise) - Material5: Phosphor Bronze, Finish\_Plating5: Nickel plating with tin over plate

### LISTING AGENCY INFO

ETL 3013270-004

FCC

UL E131600

### BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant

