

Ortronics

OR-PMD6U481U

48-port rear load maximum density Category 6 patch panel (1 rack unit). It is supplied with Clarity 6 rear load dual port panel jacks. 19" x 1.75" - OR-PMD6U481U

48-port rear load maximum density Category 6 patch panel (1 rack unit), supplied with Clarity 6 rear load dual port panel jacks, 19" x 1.75".



FEATURES

- Maximum density 110 termination
- Maximizes rack space
- Jacks support snap-in icons
- Universal wiring labels on 110 fields
- Includes rear cable management
- New positive latching dual port design

BENEFITS

- Preferred terminations load from rear of panel

Ortronics

OR-PMD6U481U

- 48 ports in 1 rack unit
- Easy designation of ports
- Supports both T568B and T568A wiring schemes
- Supports best management practices
- Flexible and secure mounting of jacks into panel

Specifications

APP INSTALL INFO

Mounting Hardware Included: Yes

Installation Tips: Terminate dual panel jacks and then rear load into the panel, dress cables to the support bar, maintaining minimum bend radius of four times the cable diameter. Secure cables with hook and loop supplied with the wire management bar.

DIMENSION INFO

Height Metric: 44.45 mm

Width Metric: 482.6 mm

Depth Metric: 101.6 mm

Height U S: 1.5 in

GENERAL INFO

Mod Jack Wiring: Universal T568A/B

Number Of Ports: 48

Color: Black with blue silkscreen

TECHNICAL INFO

Performance Rating: Category 6

CONSTRUCTION INFO

Component1: Panel - Material1: 14 awg CRS, Finish_Plating1: Black with blue silkscreen

Component2: Wire Management Bar - Material2: .125" x .320" cold rolled steel round edge flat wire, Finish_Plating2: Black

Component4: Patch Panel Mounting Screws #12-24 x 5/8" - Material4: Steel, Finish_Plating4: Black

LISTING AGENCY INFO

UL E131600

BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant