

48-port rear load maximum density patch panel, 1 rack unit, 19" x 1.75" - OR-PMD5EU481U

48-port rear load maximum density patch panel supplied with Category 5e dual rear load panel jacks that are component compliant to TIA/EIA Category 5e performance requirements. It occupies 1 rack unit, and measures 19" x 1.75". Part of the Clarity 5E link and channel solution that provides significant installed performance headroom.



FEATURES

- **Maximum density 110 termination:** Preferred terminations load from rear of panel.
- **Maximizes rack space:** 48 ports in 1 rack unit.
- **Jacks support snap-in icons:** Easy designation of ports.
- **Universal wiring labels on 110 fields:** Supports both T568B and T568A wiring schemes.
- **Includes rear cable management:** Supports best management practices.
- **New positive latching dual port design:** Flexible and secure mounting of jacks into panel.

Specifications

APP INSTALL INFO

Mounting Hardware Included: Yes

Installation Tips: Terminate dual panel jacks and then rear load into the panel, dress cables to the support bar,

maintaining minimum bend radius of four times the cable diameter. Secure cables with hook and loop supplied with the wire management bar.

DIMENSION INFO

Height Metric: 44.45 mm

Width Metric: 482.6 mm

Depth Metric: 101.6 mm

Height U S: 1.5 in

GENERAL INFO

Mod Jack Wiring: T568A/B

Number Of Ports: 48

Color: Black with green silkscreen

TECHNICAL INFO

Performance Rating: Category 5e

CONSTRUCTION INFO

Component1: Panel - Material1: 14 awg CRS, Finish_Plating1: Black with green silkscreen

Component2: Wire Management Bar - Material2: .125" x .320" cold rolled steel round edge flat wire, Finish_Plating2: Black

Component4: Patch Panel Mounting Screws #12-24 x 5/8" - Material4: Steel, Finish_Plating4: Black

LISTING AGENCY INFO

UL E131600

BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant