

Clarity 5E dual panel jack, rear load, T568A/B, 180 deg, black - OR-DJ5E00-00



Clarity 5E dual panel jacks rear load into Ortronics maximum density 48-port 1 rack unit panel and exceed Category 5e component specifications. Rear load positive latch design, secures mounting of the jack into the panel. Universal T568A/B wiring label and tapered wiring towers simplify termination.



FEATURES

- **Exceeds Category 5e component standard:** Ensures standards compliance.
- **New positive jack latching design:** Secures mounting of jacks into panel.
- **Easy to follow universal wiring label that supports T568A and T568B wiring schemes:** Quick and user-friendly, eliminates confusion.
- **New dual panel jack footprint:** Allows maximum density panel applications.
- **Icon compatible:** Supports 606 designation requirements.
- **RoHS compliant:** Lead free, green initiative.

Specifications

DIMENSION INFO

Height Metric: 36.58 mm

Ortronics

OR-DJ5E00-00

Width Metric: 14.22 mm
Depth Metric: 26.67 mm
Height U S: 1.44 in

GENERAL INFO

Category Performance Application: Category 5e/UTP
Mod Jack Wiring: T568A/B
Color: Black
Footprint: Dual Panel Jack

TECHNICAL INFO

Performance Rating: Category 5e
Wire Gauge: 22-26 AWG
Category Rating: Category 5e

CONSTRUCTION INFO

Component2: Array of eight modular dual reactance contacts - Material2: Beryllium copper, Finish_Plating2: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

LISTING AGENCY INFO

FCC
UL E131600

BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO
Buy American Act Status: Trade Agreement Act Compliant