

# HBL2310 -- Twist-Lock Receptacle



2P3W, 20A 125V, L5-20R, Black Nylon Face

## Product Specifications

**Product Type**



<b>Product Item</b>	Single Receptacle
<b>Wiring Scheme</b>	2 Pole, 3 Wire Grounding
<b>Amperage</b>	20A
<b>Voltage</b>	125V AC
<b>NEMA Configuration</b>	L5-20R
<b>Item Style</b>	Standard
<b>Device Color</b>	Black
<b>Horsepower</b>	1
<b>Terminal Clamp Material</b>	.040" (1.0 ) Brass
<b>Terminal Screw Material</b>	#10-32 Bronze (White finish on neutral screw when used)
<b>Ground Screw Material</b>	#10-32 Bronze (Green)
<b>Contact Spring Material</b>	.040" Brass

<b>Mounting Screw Material</b>	Steel-zinc-plated
<b>Cover (Top) Material</b>	Black Nylon
<b>Base Material</b>	Nylon Polyester
<b>Ground Contact Material</b>	.040" Brass
<b>Bridge (Mounting Strap) Material</b>	.050" Brass
<b>Back Plate Material</b>	.040" Brass
<b>Rivet Material</b>	Brass
<b>Auto Ground Clip Material</b>	Stainless Steel
<b>Ratings</b>	Molded into face.
<b>Dielectric Voltage Withstand</b>	2,000V minimum.
<b>Current Interrupting</b>	Certified for current interrupting at full rated current.
<b>Temperature Rise</b>	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
<b>Terminal Accommodation</b>	#14 to #8 AWG Copper Only
<b>Terminal Identification</b>	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
<b>Flammability</b>	HB or better per UL 94 or CSA 22.2 No. 0.6
<b>Operating Temperatures</b>	Maximum Continuous 75 C Minimum -40 C (w/o impact)
<b>Listings</b>	FED SPEC UL/CSA
<b>Feature Info</b>	Black nylon face.
<b>M Drawings</b>	<a href="#">Click here for M-Drawing</a>
<b>UPC Number</b>	78358523550
<b>Weight in LBs</b>	0.25

